January 13, 2025

Douglas Landing Developments
1 Forillon Cres.
Kanata, ON K2M 2W5

E-mail: g.espie@rogers.com

Attention: Dr. Gillian Espie

Re: Servicing Options Statement, Terrain Assessment and Hydrogeological Study in Support of Development
9243 McArton Road, Beckwith Township, Ontario
Pinchin File: 283258.001

Pinchin Ltd. (Pinchin) was retained through an Authorization to Proceed, signed by Dr. Gillian Espie of Douglas Landing Developments (Client), to conduct a Servicing Options Statement, Terrain Assessment and Hydrogeological Study in Support of Development at the property located at 9243 McArton Road, Beckwith Township, Ontario (hereafter referred to as the Site). The Site location is shown on Figure 1 and Figure 2 (all figures are provided in Appendix I).

The purpose of the Hydrogeological Study and Terrain Assessment in Support of Development is to fulfill the Municipality requirements for a Services Options Statement, a Terrain Analysis, and a Hydrogeological Study to be completed as components for the development application.

1.0 BACKGROUND

It is Pinchin's understanding that the approximately 54.2-acre (21.9 Hectares (ha)) Site is currently vacant as a previously severed farmland. The Site presently contains various natural features including farmland, woodland, unevaluated wetland, and drainage features. The Client intends to develop the Site into a rural residential development with amenities. The concept plan supplied by the Client indicates that the proposed subdivision will be comprised of twenty-three (23) residential lots, two (2) stormwater management lots, and one wetland block. The average lot size for the residential lots is approximately 0.60 ha.

The Municipality requires a Services Options Statement, a Terrain Analysis, and a Hydrogeological Study to be completed as components by qualified consultants and the investigations are to conform to the Ministry of Environment, Conservation, and Parks (MECP) D-5 Planning for Sewage and Water Services, an implementation guide for municipal planning, servicing, and infrastructure with a focus on sewage and water services (Provincial Policy Statement under Section 3 of the Planning Act).

2.0 SCOPE OF WORK

The scope of work outlined below is based on the guidance of the MECP D-5-3 Servicing Options Statement, MECP D-5-4 Individual On-Site Sewage Systems: Water Quality Impact Risk Assessment, MECP D-5-5, Private Wells: Water Supply Assessment, discussions with Fotenn, and information supplied to Pinchin by the Client. The scope of work consisted of the following activities.

The Servicing Options Statement followed MECP Guideline D-5-3 including:

- Evaluation of proximity of existing or committed full municipal services or communal services and the ultimate potential for future connection to full municipal services or communal services for the whole area proposed for development;
- Review of the proposed development as being part of, or anticipated as being one of a number of proposals for the same development area, in which case the evaluation of servicing options will not be isolated to the site-specific proposal, but will be completed within the context of the development potential; and,
- Review of the environmental suitability of the Site for the proposed services based on information accessible at a municipal scale that can be applied to the proposed Site proposal including:
    - environmental constraints;
    - suitability of the terrain of the Site; and
    - performance of services in similar developments in the surrounding area; and the scale (total areal extent), density, and type of use proposed for the development.

The Terrain Assessment followed MECP Guideline D-5-4 including:

- Discussion and input of proposed locations for groundwater supply wells and septic bed locations with the Client and/or their representative;
- Excavation of up to fifteen (15) test pits across the area of the proposed development. Locations were selected to provide adequate coverage of any anticipated changes in soil type or depth to bedrock or saturated conditions. Where possible the test pits were excavated in the area identified as the preferred location for inground disposal of septic effluent on the lots;
- Test pits were excavated to a maximum depth of approximately 1.5 m below ground surface, or until bedrock or the water table was intersected;

- For each test pit, the soil type, texture, and other characteristics were logged and documented with photographs; and
- Up to 4 samples selected based on representation of the Site areas were collected and submitted to a materials testing laboratory for grain size analysis and estimate of percolation rates.

Every proposed development involving individual on-site sewage systems requires an assessment of the potential impact to groundwater resources. The purpose of the assessment is to ensure that the combined effluent discharges from all the individual on-site sewage systems in a development will have a minimal effect on the groundwater and the present or potential use of the adjacent property. The assessment involves a three-step process with Step 1 being review of lot sizes. Developments consisting of lots which average 1 hectare (with no lot being smaller than 0.8 ha) may not require additional evaluation for areas that are not hydrogeologically sensitive. However, it is noted that the proposed development includes many lots which are less than 0.8 hectare, and as such additional assessment steps as per D-5-4 are required. This requirement will be met through evaluating the isolation of the aquifer and assessing the risk that the development's individual on-site systems will cause concentrations of nitrate-nitrogen in groundwater to exceed 10 mg/L at the downgradient property boundary.

Hydrogeology Study

Based on the Site size, Guideline D-5-5 prescribes a minimum of four (4) test wells as required for completion of the Hydrogeology Study. Guideline D-5-5 notes that the aerial distribution of test wells must be such that hydrogeological conditions across the Site are adequately represented. It is Pinchin's opinion that pumping tests on a minimum of four (4) test wells were required for appropriate evaluation of the Site. Further, it is noted that previously completed hydrogeologic investigations in support of the residential development to the east of the Site provides additional information that was incorporated into the study.

The Hydrogeology Study followed MECP Guideline D-5-5 and included:

- Selection of areas where wells will be installed to provide adequate coverage of the proposed development. The locations of the wells were coordinated with the Client and used the proposed lot fabric for positioning such that the test wells are in suitable locations to become long-term supply wells for the lots;
- After the wells had been drilled, a qualified well contractor licensed with the MECP temporarily installed a pump in each well and disinfected each well in accordance with procedures outlined in the MECP Water Supply Wells: Requirements and Best Practices Manual;

- Constant discharge pumping tests at each of the four wells were completed sequentially. Each pumping test was for a minimum of six hours and at a flow rate required to demonstrate adequate water quantity for the proposed use;
- During the pumping tests the water levels in the pumping well and the adjacent wells on the Site were monitored and recorded. The water levels in select existing private wells close to the Site were monitored where permission from the owner was received;
- One water quality sample was collected from each of the pumping wells during the pumping phase of the constant discharge pumping test. The Sample was collected just prior to cessation of pumping at six (6) hours;
- The water quality samples were submitted to an independent, accredited laboratory for analysis of bacteriological, general inorganic and metal parameters. Results were compared to the Ontario Drinking Water Quality Standards (ODWQS) to assess the quality of the water supply; and
- After the pumping phase of the test is completed the recovery of the water level in each well was monitored.

3.0 METHODOLOGY

Constant Discharge Pumping Tests

The Client retained Air Rock Drilling Co. Ltd. (Air Rock), to install the wells on the Site and to complete the well disinfection, pump installation, and operation for the pumping test work. Dedicated is a licenced well contractor and Site work was completed by licenced well technicians. Water samples were collected by a Pinchin staff member who works under supervision of a registered and practicing professional geoscientist (P.Geo.) in Ontario.

Prior to the pumping test on each well, the well contractor disinfected the well by chlorination as per shock chlorination procedure *Well Regulations – Well Disinfection (Technical Bulletin 1 of 11)*. After approximately 14 to 20 hours of contact time (i.e., the next day) the pumping test was conducted. The pumping test and groundwater sampling event were completed by placing a ¾ hp pump to approximately 5 to 10 m above the bottom of the well. The pump was powered by a portable generator. The pumping rate was controlled by a dedicated flow restrictor that maintained the discharge rate for the duration of the pumping test and the pumped water was discharged to the ground approximately 15 m from the well, in a direction that was observed to slope away from the well head. The pumping rate was selected based on well yield as determined during the 1-hr pumping test completed by the Well Contractor at the time of the well installation and the D-5-5 minimum requirement of 13.75 Lpm and to ensure that the well could

sustain the pumping rate for the duration of the pumping test. The duration of the pumping test was 360 mins (6 hrs).

After pumping duration of the test was met, the free chlorine in the groundwater discharge was measured in the field using a Hach DR900 multiparameter portable colorimeter, and if below (0.0 mg/L), Pinchin staff collected a groundwater sample from the well for water quality analysis. If there was still free chlorine in the well, pumping continued until the free chlorine in the groundwater discharge was measured in the field, and if below (0.0 mg/L), then a sample was collected. Samples were collected in laboratory supplied, single-use bottles and were stored on ice and delivery to the laboratory for analysis.

To assess the potential for interference from the pumping activities at the wells located at the Site, pumping tests were completed sequentially on the four Site wells. When one of the Site wells was being pumped the water levels in the other three wells on the Site were monitored. Efforts were made to gain permission to monitor water levels using data loggers in private wells near the Site; namely from nearby residents located along Ridgemont Dr., to the east of the Site. Three residents granted permission for their wells to be included in the monitoring program. The locations of the three domestic supply wells included in the monitoring program are shown on Figure 2 and are summarized below:

- 244 Ridgemont Dr. Approximately 130 m northeast of the Site. The well is a drilled well with well tag A309683. Based on well record in the MECP Water Well database this well was installed on March 31, 2021. The well is 43.7 m deep in completed in limestone with layers of shale and sandstone. The estimated well production at the time of well installation was 40.9 Litres per minute (Lpm) and the static water level was 8.95 metres below top of casing (mbtoc).
- 270 Ridgemont Dr. Approximately 95 m east of the Site. The well is a drilled well with well tag A309684. Based on well record in the MECP Water Well database this well was installed on March 31, 2021. The well is 53.6 meters deep and completed in limestone with layers of sandstone. The estimated well production at the time of well installation was 36.4 Lpm and the static water level was 9.2 mbtoc.
- 322 Ridgemont Dr. Approximately 65 m east of the Site. The well is a drilled well with well tag A296823. A review of the MECP Water Well Database did not locate a well record for this well. At the time of the installation of the data logger for the investigation the static water level was 10.79 mbtoc.

Groundwater samples were submitted to Caduceon Environmental Laboratories (Caduceon) for the ‘D-5-5 Subdivision Suite’ including bacterial parameters. Caduceon is an independent laboratory accredited by the Standards Council of Canada and the Canadian Association for Laboratory Accreditation. Formal

chain of custody records of the sample submissions were maintained between Pinchin and the staff at Caduceon.

Test Pitting

The Client retained Dedicated Environmental Services Inc. (Dedicated) to complete test pitting as part of the Terrain Assessment portion of this project. Using a mini-excavator, nine (9) test pits were excavated to assess depth to bedrock, soil character and saturation conditions. Additionally, ten (10) boreholes were advanced as part of a separate geotechnical investigation and those data are included in this study. The locations of the test pits and boreholes are shown on Figure 2. The test pits were examined by Pinchin staff who logged the soil stratigraphy, recorded depth to bedrock, and collected representative samples. A selection of samples that characterized the soils encountered across the Site were submitted to Malroz Engineering Inc. Laboratory (Malroz Laboratory) for grain size analysis and percolation (T-time) estimate. Malroz Laboratory is a certified laboratory with the Canadian Council of Independent Laboratories (CCIL).

4.0 QA/QC PROTOCOLS

Various quality assurance/quality control (QA/QC) protocols were followed to ensure that representative groundwater samples were obtained, and that representative analytical data were reported by the laboratory.

Field QA/QC protocols that were employed by Pinchin included the following:

- The groundwater samples were placed in laboratory-supplied sample containers;
- Groundwater samples were collected within the last 10 minutes of the pumping test and after ensuring that free chlorine in the groundwater discharge at the well was below field detection (0.0 mg/L). If the free chlorine level was not yet below detection at the end of the scheduled pumping duration, then the pumping continued until the free chlorine in the discharge water was below detection, at which time the sample was collected;
- The groundwater samples were placed in a cooler on ice immediately upon collection, with appropriate sample temperatures maintained prior to submission to the laboratory;
- The soil samples were placed in single use, sealable sampling bags which were placed in a cooler;
- Dedicated and disposable nitrile gloves were used for sample collection; and

- Sample collection and handling procedures were performed in general accordance with the *MECP Sampling Guideline*, the *APGO Guideline* and Pinchin's SOPs for groundwater sampling.

Groundwater Supply – Regulatory Criteria

The wells are for a domestic water supply, as such the analytical results were compared to the Ontario Drinking Water Standards (ODWQS) health related criteria (MAC) and to the ODWQS aesthetic and operational criteria (AO and OG) as outlined in MECP Guideline *D-5-5 Private Wells: Water Supply Assessment* (D-5-5).

5.0 FINDINGS

Review of Servicing in the Area

No municipal services abut the Site. The closest municipal servicing is located approximately 5 km to the west in Carleton Place. There are no plans to extend this servicing at this time.

There are approximately 40 residential properties present along Ridgemont Dr. which runs north-southeast of the site, approximately 7 residential lots along Douglas Side Road, and another approximately 7 residential lots along McArton Road to the north of the Site. These areas, and other individual residences along County Road #26, are serviced by individual water and wastewater systems.

Based on review of servicing in the area it is determined that the most appropriate servicing for the proposed development is individual well and septic.

Review of Potable Water Supply in the Area

The suitability of individual drilled wells for water supply for the proposed development was assessed by reviewing the available water well records within approximately 500 m of the proposed development boundary. The MECP Well Record Database was reviewed, and a total of 40 well records were identified. The well record numbers and locations are shown on Figure 3, and a summary of well characteristics is included as Table 1 in Appendix II along with the individual well records.

The well records indicated that all the wells were drilled wells. Of the 40 well records where lithology was present, all wells terminated within limestone. It is noted that the well records for many of the wells indicated layers of shale or sandstone within the limestone unit. This may represent just shale layers which are not atypical for the limestone in the area or in some cases be indicative of transition to the sandstone unit that underlays the limestone in the area.

The depth of completion for the drilled wells ranged from 15.8 m to 136.4 m, with the average well depth being 43.0 m. The majority (78%) of the wells were completed between 30 m and 60 m below ground surface (mbgs).

Overburden thickness is generally shallow ranging from 0.0 m to 2.9 m. The average thickness for the overburden was 1.1 m and approximately 88% of the well records indicating overburden thickness less than 2.0 m.

Water was first found at depths ranging from 15.8 m to 71.0 m. Approximately 85% of the well records listed the depth of water first found to be in the range of 15 m to 40 m.

Pumping rates recommended by the drillers at the time of well installation were listed on all of the well records. The recommended pumping rates ranged from 22.7 liters per minute (Lpm) to 136.4 Lpm, with an average recommended pumping rate of 54.4 Lpm. These rates are based on short-term testing but demonstrate the variability and typically high yield in the potable water supply in the vicinity of the Site.

Review of Water Well Records for Site

The well records for the four wells installed on the Site are included in Appendix II. The locations of the wells are shown on Figure 2. The wells were completed by Air Rock Drilling Co. Ltd. (Air Rock), a registered well contractor in Ontario.

Well #1 (A360958)

The well is a drilled well. Steel casing (15.9 cm dia.) was installed to a depth of 12.2 m with a stickup of approximately 0.61 m above ground surface. The annular space was sealed by pressure grouting from ground surface to 12.2 m. The stratigraphy at the well location was described as 0.91 m of sandy clay with stones overlaying limestone bedrock. The well was advanced 29.6 m into the limestone to completion depth of 30.5 m.

Water was found at 20.4 mbgs and 28 mbgs in the limestone unit. The static water level at the time of well completion was 7.74 meters below top of casing (mbtoc).

At the time of well installation the well driller completed a one-hour pumping test at 90.9 Lpm. This rate and duration of testing corresponds to a water taking of approximately 5,454 litres. The recommended pumping rate noted on the well record was 90.9 Lpm. During this pumping test the water level in the well decreased 0.20 m and recovered to the original static level within 3 minutes after pumping was stopped.

This well meets O. Reg. 903 requirements with respect to construction based on Site observations and review of the well record.

Well #2 (A360957)

The well is a drilled well. Steel casing (15.9 cm dia.) was installed to a depth of 12.2 m with a stickup of approximately 0.61 m above ground surface. The annular space was sealed by pressure grouting from ground surface to 12.2 m.

The stratigraphy at the well location was described as 0.91 m of sand and stones overlaying limestone bedrock. The well was advanced 41.8 into the limestone to a completion depth of 42.8 m.

Water was found at 40.5 mbgs in the limestone. The static water level at the time of well completion was 7.13 mbtoc.

At the time of well installation the well driller completed a one-hour pumping test at 54.6 Lpm. This rate and duration of testing corresponds to a water taking of approximately 3,276 litres. The recommended pumping rate on the well record is 54.6 Lpm. During this pumping test the water level in the well decreased 0.67 m and recovered to the original static level within 5 minutes after pumping was stopped.

This well meets O. Reg. 903 requirements with respect to construction based on Site observations and review of the well record.

Well #3 (A360960)

The well is a drilled well. Steel casing (15.9 cm dia.) was installed to a depth of 12.2 m with a stickup of approximately 0.61 m above ground surface. The annular space was sealed by pressure grouting from ground surface to 12.2 m.

The stratigraphy at the well location was described as 0.61 m of sand overlaying limestone bedrock. The well was advanced 51.8 m into the limestone to a completion depth of 51.2 m.

Water was found at a depth of 48.8 m and 50.3 m in the limestone unit. The static water level at the time of well completion was 7.13 mbtoc.

At the time of well installation the well driller completed a one-hour pumping test at 90.9 Lpm. This rate and duration of testing corresponds to a water taking of approximately 5,454 litres. The recommended pumping rate noted on the well record was 90.9 Lpm. During this pumping test the water level in the well decreased 0.15 m and recovered to the original static level within 2 minutes after pumping was stopped.

This well meets O. Reg. 903 requirements with respect to construction based on Site observations and review of the well record.

Well #4 (A360959)

The well is a drilled well. Steel casing (15.9 cm dia.) was installed to a depth of 12.2 m with a stickup of approximately 0.61 m above ground surface. The annular space was sealed by pressure grouting from ground surface to 12.2 m.

The stratigraphy at the well location was described as 0.61 m of sand overlaying limestone bedrock. The well was advanced 54.3 m into the limestone to a completion depth of 54.9 m.

Water was found at 23.5 mbgs and 52.7 in the limestone unit. The static water level at the time of well completion was 5.64 mbtoc.

At the time of well installation the well driller completed a one-hour pumping test at 45.7 Lpm. This rate and duration of testing corresponds to a water taking of approximately 2,742 litres. The recommended pumping rate noted on the well record was 45.7 Lpm. During this pumping test the water level in the well decreased 1.77 m and recovered to the original static level within 20 minutes after pumping was stopped.

This well meets O. Reg. 903 requirements with respect to construction based on Site observations and review of the well record.

5.3 Constant Discharge Pumping Tests

The methodology for the pumping tests is described in a previous section. Information specific to schedule and setup of the individual pumping tests are summarized in Table 2 summarized below.

Table 2: Summary Pumping Test Setup for Each Test Well.

Pumping Well ID	Pumping Test Date & Start Time	Pumping Rate (Lpm)	Pumping Duration (minutes)	Monitoring Network: Well ID, Distance, and Direction from Pumping Well
Well #1 (A360958)	25-Oct-2024 4:00 AM	90.9 Lpm	360 min	Well #2 A360957, 184 m, N. Well #3 A360959, 351 m, W. Well #4 A360960, 473 m, W. 322 Ridgemont Dr., 185 m, NE. 270 Ridgemont Dr.,244 m, NE. 244 Ridgemont Dr., 346 m. SE.
Well #2 (A360957)	24-Oct-2024 5:15 AM	90.0 Lpm	360 min	Well #1 (A360958), 184 m, S. Well #3 A360959, 374 m, SW. Well #4 A360960, 541 m, SW. 322 Ridgemont Dr., 318 m, SE. 270 Ridgemont Dr.,175 m, E. 244 Ridgemont Dr., 200 m. NE.

Pumping Well ID	Pumping Test Date & Start Time	Pumping Rate (Lpm)	Pumping Duration (minutes)	Monitoring Network: Well ID, Distance, and Direction from Pumping Well
Well #3 (A360960)	23-Oct-2024 5:45 AM	90.9 Lpm	360 min	Well #1 (A360958), 351 m, E. Well #2 A360957, 374 m, NE. Well #4 A360960, 189 m, SW. 322 Ridgemont Dr., 560 m, SE. 270 Ridgemont Dr.,535 m, E. 244 Ridgemont Dr., 569 m. NE.
Well #4 (A360959)	21-Oct-2024 (6:30 AM)	68.2 Lpm	360 min	Well #1 (A360958), 473 m, E. Well #2 A360957, 541 m, NE. Well #3 A360959, 189 m, NE. 322 Ridgemont Dr., 632 m, E. 270 Ridgemont Dr., 688 m, NE. 244 Ridgemont Dr., 742 m. NE.

Well #1 (A360958)

A plot of water drawdown during the Well #1 pumping test is included as Figure 4. During the 6 hours of pumping at 90.9 Lpm, a total of approximately 32,724 L of water were pumped from the well. The maximum drawdown observed in the pumping well was to 9.37 mbtoc (a drawdown of 0.16 m from static water level). When pumping stopped, the water level in the well recovered to greater than 95% within 240 minutes. A summary of the pumping test results is included as Table 3 below.

Table 3: Summary of Pumping Test for Well #1 (A360958).

Duration of Pumping Test (min)	Pumping Rate (Lpm)	Static Water Level (mbtoc)	Maximum Drawdown (mbtoc)	Maximum Drawdown (m)	Total volume of water pumped (L)	Recovery in 10 min (%)	Time to 95+% Recovery (min)
360	90.9	9.22	9.38	0.16	32,724	50 %	240 min

Well #2 (A360957)

A plot of water drawdown during the Well #2 pumping test is included as Figure 5. During the 6 hours of pumping a total of approximately 32,724 L of water were pumped from the well. The maximum drawdown observed in the pumping well was to 9.10 mbtoc (a drawdown of 0.48 m from the static water level). When pumping stopped, the water level in the well recovered to 93% of static within 60 minutes. A summary of the pumping test is included as Table 4 below.

Table 4: Summary of Pumping Test for Well #2 (A360957).

Duration of Pumping Test (min)	Pumping Rate (Lpm)	Static Water Level (mbtoc)	Maximum Drawdown (mbtoc)	Maximum Drawdown (m)	Total volume of water pumped (L)	Recovery in 4 min (%)	Time to 93% Recovery (min)
360	90.9	8.63	9.10	0.48	32,724	80%	60 min

Well #3 (A360960)

A plot of water drawdown during the Well #3 (A360960) pumping test is included as Figure 6. During the 6 hours of pumping a total of approximately 32,724 L of water were pumped from the well. The maximum drawdown observed in the pumping well was to 8.78 mbtoc (a drawdown of 0.07 m from the static water level). When pumping stopped, the water level in the well fully recovered to the original static level 50 minutes. A summary of the pumping test is included as Table 5 below.

Table 5: Summary of Pumping Test for Well #3 (A360960).

Duration of Pumping Test (min)	Pumping Rate (Lpm)	Static Water Level (mbtoc)	Maximum Drawdown (mbtoc)	Maximum Drawdown (m)	Total volume of water pumped (L)	Recovery in 10 min (%)	Time to 100% Recovery (min)
360	90.9	8.71	8.78	0.07	32,724	67%	50 min

Well #4 (A360959)

A plot of water drawdown during the Well #4 pumping test is included as Figure 7. During the 6 hours of pumping at 68.2 Lpm a total of approximately 24,552 L of water were pumped from the well. The maximum drawdown observed in the pumping well was to 9.03 mbtoc (a drawdown of 2.21 m from the static water level). When pumping stopped, the water level in the well fully recovered to the original static level 240 minutes (4 hours). A summary of the pumping test is included as Table 6 below.

Table 6: Summary of Pumping Test for Well #4 (A360959).

Duration of Pumping Test (min)	Pumping Rate (Lpm)	Static Water Level (mbtoc)	Maximum Drawdown (mbtoc)	Maximum Drawdown (m)	Total volume of water pumped (L)	Recovery in 15 min (%)	Time to 95+% Recovery (min)
360	68.2	6.83	9.03	2.21	24,552	70%	240 min

Potential for Well Interference

During each pumping test the other three wells on the Site were instrumented with data loggers to record the water levels in the wells. Additionally, three nearby domestic supply wells along Ridgemont Dr. were included in the monitoring program. The street address of the domestic supply wells monitored and their distance from the pumping wells are included in Table 2.

The private domestic wells monitored during the test remained in service and short duration drawdown and recovery events can be seen in the data. These events reflect the pumps in the domestic wells coming on to repressurize the water supply system at the residences and are not drawdown resulting from the pumping well activities.

Overall, the amount of drawdown in the monitoring network wells that is attributable to pumping activities was small and ranged from zero (no interaction at all) to a maximum of 0.12 m. Approximately 75% of all the interactions across the four pumping tests were less than 0.05 m of attributable drawdown from pumping activities.

Observations regarding potential well interference are summarized below in Table 7.

Table 7: Summary of Findings for Potential Well Interference.

Pumping Well ID	Pumping Rate (Lpm)	Pumping Duration (min)	Monitoring Network: Well ID, Distance and Direction from Pumping Well	Drawdown Attributable to Pumping Activities (m)
Well #1 (A360958)	90.9 Lpm	360 min	Well #2 A360957, 184 m, N.	0.11
			Well #3 A360959, 351 m, W.	0.03
			Well #4 A360960, 473 m, W.	None
			322 Ridgemont Dr., 185 m, NE.	0.11
			270 Ridgemont Dr.,244 m, NE.	0.04
			244 Ridgemont Dr., 346 m. SE.	0.10
Well #2 (A360957)	90.9 Lpm	360 min	Well #1 (A360958), 184 m, S.	0.12
			Well #3 A360959, 374 m, SW.	0.04
			Well #4 A360960, 541 m, SW.	0.02
			322 Ridgemont Dr., 318 m, SE.	0.12
			270 Ridgemont Dr.,175 m, E.	0.04
			244 Ridgemont Dr., 200 m. NE.	0.12
Well #3 (A360960)	90.9 Lpm	360 min	Well #1 (A360958), 351 m, E.	None
			Well #2 A360957, 374 m, NE.	0.02
			Well #4 A360960, 189 m, SW.	None
			322 Ridgemont Dr., 560 m, SE.	0.02
			270 Ridgemont Dr.,535 m, E.	0.04
			244 Ridgemont Dr., 569 m. NE.	0.02
Well #4 (A360959)	68.2 Lpm	360 min	Well #1 (A360958), 473 m, E.	0.02
			Well #2 A360957, 541 m, NE.	0.02
			Well #3 A360959, 189 m, NE.	None
			322 Ridgemont Dr., 632 m, E.	0.02
			270 Ridgemont Dr., 688 m, NE.	None
			244 Ridgemont Dr., 742 m. NE.	0.02

Plots of drawdown versus time for the monitoring wells are provided as follows:

- **Well #1** (A360958), Figure 8a and Figure 8b;
- **Well #2** (A360957), Figure 9a and Figure 9b (reduced y-axis);
- **Well #3** (A360960), Figure 10a and Figure 10b (reduced y-axis); and
- **Well #4** (A360959), Figure 11a and Figure 11b (reduced y-axis).

Based on these data no adverse interference between wells on the proposed development and existing domestic supply wells is to be anticipated.

5.4 Water Supply – Quality

The summary of the groundwater analytical results along with the ODWQS Health Related Maximum Allowable Concentration (MAC) and Aesthetic Objective (AO) as well as the Aesthetic Limits as listed in the MECP D-5-5 Guideline are presented in Table 8 in Appendix III. The laboratory Certificate of Analysis for the groundwater samples is provided in Appendix IV. Residual chlorine was measured in the field and confirmed to be below detection prior to collection of the raw groundwater samples prior to cessation of pumping.

Well #1 (A360958)

Water quality results for the raw groundwater sample collected from Well #1 (A360958) prior to cessation of the pumping test met the applicable criteria:

- Health Related Parameters (MAC)
    - The analytical result for sodium was 39.8 mg/L compared to the Warning Level MAC of 20 mg/L. This health-related limit is a "warning level" only. Exceedance calls for a recommendation that the local Medical Officer of Health be notified in order to alert persons with medical conditions or dietary restrictions.
- Aesthetic Objective (AO) & Operational Guideline (OG) Related Parameters
    - The analytical result for manganese was 0.144 mg/L compared to the AO criteria of 0.05 mg/L; and
    - The analytical result for hardness exceeded was 343 mg/L compared to the OG of 80-100 mg/L. Hardness did not exceed the AO criteria of 500 mg/L.

The raw water quality is considered good and suitable as a potable water source. If the user finds the elevated hardness to be unpalatable or cause objectional staining, treatment systems such as a water softened could be incorporated into the water treatment system. Treating hardness usually results in a decrease in manganese as well. If sodium levels poise a dietary or medical concern an undercounter reverse osmosis system connected to a dedicate drinking water spigot could be part of the water treatment system.

Well #2 (A360957)

Water quality results for the raw groundwater sample collected from Well #2 (A360957) prior to cessation of the pumping test met the applicable criteria, with the following exceptions:

- Health Related Parameters (MAC)
  - All analyzed parameters complied with MACs.
- Aesthetic Objective (AO) & Operational Guideline (OG) Related Parameters
  - The analytical result for hardness was 311 mg/L compared to the OG of 80-100 mg/L. Hardness did not exceed the AO criteria of 500 mg/L.

The raw water quality is considered good and suitable as a potable water source. If the user finds the elevated hardness to be unpalatable or cause objectional staining, treatment systems such as a water softener could be incorporated into the water treatment system.

Well #3 (A360960)

Water quality results for the raw groundwater sample collected from Well #3 (A360960) prior to cessation of the pumping test met the applicable criteria:

- Health Related Parameters (MAC)
  - All analyzed parameters complied with MACs.
- Aesthetic Objective (AO) & Operational Guideline (OG) Related Parameters
  - The analytical result for hardness was 357 mg/L compared to the OG of 80-100 mg/L. Hardness did not exceed the AO criteria of 500 mg/L.

The raw water quality is considered good and suitable as a potable water source. If the user finds the elevated hardness to be unpalatable or cause objectional staining, treatment systems such as a water softener could be incorporated into the water treatment system.

Well #4 (A360959)

Water quality results for the raw groundwater sample collected from Well #4 (A360959) prior to cessation of the pumping test met the applicable criteria, with the following exceptions:

- Health Related Parameters (MAC)
  - All analyzed parameters complied with MACs.
- Aesthetic Objective (AO) & Operational Guideline (OG) Related Parameters
  - The analytical result for hardness was 385 mg/L compared to the OG of 80-100 mg/L. Hardness did not exceed the AO criteria of 500 mg/L.

The raw water quality is considered good and suitable as a potable water source. If the user finds the elevated hardness to be unpalatable or cause objectional staining, treatment systems such as a water softener could be incorporated into the water treatment system.

5.5 Water Treatment Options

- **Preventative Disinfection -** As a preventative and best management practice it is recommended that any water supply system utilizing an individual well as the supply source include water disinfection. The most common treatment to meet this recommendation is disinfection by UV with appropriate particulate pre-filtration. Such systems are readily available.
- **Hardness -** Hardness has an Operational Guideline of 80 to 100 mg/L, a range considered to provide an acceptable balance between corrosion and incrustation and to aid in source selection when applicable. Water supplies with a hardness greater than 200 mg/L are considered poor but tolerable. Hardness in excess of 500 mg/L in drinking water is unacceptable for most domestic purposes however, neither the MECP D-5-5 nor the ODWQS guidance provide an upper limit for treatability. The analytical result for hardness for samples collected from wells ranged from 272 mg/L to 332 mg/L. If the user finds the water unpalatable or wishes to reduce any scaling that may occur, an off-the-shelf water softener solution would readily provide treatment. Such systems are readily available.
- **Manganese** - The Aesthetic Objective (AO) for manganese is 0.05 mg/L. manganese is objectionable in water supplies because it can stain laundry and fixtures black, and at excessive concentrations causes undesirable tastes in beverages. Manganese is present in some groundwaters because of chemically reducing underground conditions coupled

with presence of manganese mineral deposits. A water softener is often the best tool for removing manganese. The water softener can handle significant quantities of manganese, but it only works well if all the manganese is un-precipitated. Alternatively, there are a variety of filter systems available that may be more effective depending on the overall water chemistry.

A water treatment professional should be consulted for appropriate equipment sizing and treatment options.

Site Suitability for In-Ground Wastewater Disposal

Nine test pits were excavated across the Site to investigate the suitability of the Site for in-ground wastewater disposal. On Dec 2, 2024, the test pits excavated by a contractor retained by the Client using a Kubota min-excavator. The test pits were examined by Pinchin staff who logged the soil stratigraphy, recorded depth to bedrock, and collected representative samples.

Based on the observations made on the 9 test pits, the overburden can be described as shallow with the overburden thickness ranging from 0.15 m to 0.30 m, with the exception of test pit TP-4 which was advanced to 1.98 mbgs and did not encounter bedrock. The limestone bedrock surface has some degree of surficial weathering. The average overburden thickness was approximately 0.44 m. The overburden is a brown silty sand with some gravel. The overburden was loose and damp. Groundwater was not encountered in any of the test pits. Table 9 describes the stratigraphy observed in each of the test pits.

Samples from TP-1, TP-5, TP-7, and TP-8 were submitted to Malroz Engineering Inc. Laboratory (Malroz Laboratory) for grain size analysis and percolation (T-time) estimate. Results of the grain size analysis are included as in Appendix IV.

The sample collected from test pit TP-1 (0.05 m to 0.15 m) was comprised of approximately 4% gravel, 64 % sand, and 32% silt and clay. The material was categorized as silty SAND with trace gravel. The estimated T-time from the sample was 8 to 20 min/cm.

The sample collected from TP-5 (0.05 m to 0.30 m) was comprised of approximately 14% gravel, 63% sand, 24% silt and clay. The material was categorized as silty Clayey SAND with some gravel. The estimated T-time from the sample was 8 to 20 min/cm.

The sample collected from TP-7 (0.05 m to 0.15 m) was comprised of approximately 15% gravel, 66% sand, and 18% silt and clay. The material was categorized as SAND, some gravel, some silt and clay. The estimated T-time from the sample was 8 to 20 min/cm.

The sample collected from TP-8 (0.05 m to 0.30 m) was comprised of approximately 10% gravel, 62% sand, and 28% silt and clay. The material was categorized as silty, clayey SAND with some gravel. The estimated T-time from the sample was 8 to 20 min/cm.

For Class IV systems, the Ontario Building Code (OBC) requires a minimum of 900 mm (0.900 m) separation from the base of the gravel layer of the bed to the bedrock (or saturated overburden conditions). This thickness requirement of overburden was only observed in one test pit; TP-4 where bedrock was not encountered above 1.98 m, where excavation stopped.

Table 9 Test Pit Stratigraphy and Observations.

Test Pit ID	Easting	Northing	Interval (mbgs)	Description
TP-1	415179	5003150	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 - 0.15	Brown Silty Sand with small roots. Loose. Dry.
			0.15	Limestone Bedrock. Dry.
TP-2	415201	5003246	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 - 0.20	Brown Silty Sand. Loose. Dry.
			0.20	Limestone Bedrock. Dry.
TP-3	415065	5003195	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 - 0.30	Brown Silty Sand. Loose. Dry.
			0.30	Limestone Bedrock. Dry.
TP-4	414986	5003218	0 - 0.15	Topsoil with corn stalk. Loose. Dry.
			0.15 - 0.30	Brown Silty Sand. Loose. Dry.
			0.30 - 1.98	Brown Silty Sand. Loose with Gravel. Dry.
			1.98	Bedrock not encountered.
TP-5	414997	5003117	0 - 0.05	Topsoil with small roots. Loose. Damp.
			0.05 - 0.30	Brown Silty Sand. Loose. Dry.
			0.30	Limestone Bedrock. Dry.
TP-6	415365	5003468	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 0.30	Brown Silty Sand. Loose. Dry.
			0.30	Limestone Bedrock. Dry.
TP-7	415398	5003369	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 - 0.15	Brown Silty Sand with small roots. Loose. Dry.
			0.15	Limestone Bedrock. Dry.
TP-8	415440	5003281	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 0.30	Brown Silty Sand with small roots. Loose. Dry.
			0.30	Limestone Bedrock. Dry.

Test Pit ID	Easting	Northing	Interval (mbgs)	Description
TP-9	415496	5003297	0 - 0.05	Topsoil with grass roots. Dry.
			0.05 - 0.30	Brown Silty Sand with small roots. Loose. Dry.
			0.30	Limestone Bedrock. Dry.

Notes: Coordinates are in Zone T18. The bold and shaded description indicates the sample was submitted for analysis.

As a component of a geotechnical investigation completed on the Site by Pinchin, ten boreholes were advanced to bedrock across the Site. The location of the boreholes are shown on Figure 2 and the borehole logs are included in Appendix IV. Based on the borehole logs the depth to bedrock ranged from 0.15 m to 0.61 m, with an average overburden thickness of 0.44 m.

It is Pinchin's understanding that the Municipality requires a minimum of 0.25 m (10") of natural material to be present which can be scarified prior to construction of the bed. If the 0.25 m of natural material is not present, then additional lower permeability material must be incorporated in the base of the system design as well. Based on these requirements additional material would be needed at some of the lots for Class IV systems.

A tertiary system has system specific design criteria to allow for less imported material, and in some cases a less elevated mound. This may make a tertiary system a preferred cost or space saving approach. A variety of tertiary systems are approved with some specifically designed to be employed in shallow soil conditions. Additional costs associated with tertiary systems may be at least partially offset by the requirement for additional imported material that would be required for a Class IV system to address the shallow overburden conditions. The reduced footprint associated with a tertiary system can also provide more flexibility in location on the lot. A tertiary system also provides a greater overall degree of wastewater treatment and thereby increased protection for the environment.

If sufficient thickness of natural material is present, and OBC and municipal design requirements are incorporated into the system design, then Class IV systems are adequate for wastewater treatment servicing at the Site. Placement of systems must meet all OBC setbacks. Based on the percolation rates obtained during this investigation, Class IV system beds would require on the order of 300 m^2 of area for a 4-bedroom single family dwelling. More refined sizing would be calculated by the septic designer based on daily flow calculations made from actual building design plans, but for the purpose of assessing if there is adequate space on the proposed lots for the systems, these estimated areas are more than sufficient to assess whether sufficient space on the lots is present.

Each proposed lot has sufficient area for a primary septic infiltration bed location and an alternative location. Specific location of the primary and alternate septic infiltration bed as well as the system selection and design are specific to the dwelling design and size which are beyond the scope of this study.

Assessment of Potential for Groundwater Impact by on-Site Sewage System

The three-step procedure outlined in the MECP guideline: *D-5-4 Individual On-Site Sewage Systems: Water Quality Impact Risk Assessment* was used to assess groundwater impact potential from on-site sewage systems for the proposed development.

The purpose of the assessment is to ensure that the effluent discharges from the individual on-site sewage systems will have a minimal effect on the groundwater and the present or potential use of the adjacent property. For the purposes of the D-5-4 Guideline, the Ontario Drinking Water Objective (ODWO) of 10 mg/L of nitrate-nitrogen is used as an indicator of groundwater impact potential.

The assessment involves a three-step process. The need to advance to the next step depends on not meeting conditions defined in the previous step.

For developments where the lot size for each private residence within the development is one hectare or larger, the risk that the boundary limits imposed by these guidelines may be exceeded by individual systems is considered acceptable in most cases. Developments consisting of lots which average 1 hectare (with no lot being smaller than 0.8 ha), may not require a detailed hydrogeological assessment, provided that it can be demonstrated that the area is not hydrogeologically sensitive. In such circumstances, it is the responsibility of the proponent to obtain a professional analysis from a qualified consultant that the area is not hydrogeologically sensitive.

It is assumed that attenuative processes within a one-hectare lot will be sufficient to reduce the nitrate-nitrogen to an acceptable concentration in groundwater below adjacent properties. It should be noted that sufficient attenuative processes may not be present in hydrogeologically sensitive environments, or where there is little water surplus available.

Step 1 – Lot Size Considerations

For developments where the lot size for each private residence within the development is one hectare (ha) or larger, the risk that the boundary limits imposed by these guidelines may be exceeded by individual systems is considered acceptable in most cases.

Based on the conceptual Site design provided by the client, the proposed lot sizes range from approximately 0.40 ha to 1.43 ha. The average lot size is approximately 0.60 ha.

The average lot size is less than 1 ha, and the smallest lot is less than 0.8 ha. The proposed development does not satisfy Step 1, and the assessment must proceed to Step 2.

Step 2 - System Isolation Considerations

Where proposed lot sizes are less than one hectare, the proponent and/or the consultant is/are responsible for assessing the potential risk to groundwater. Developments will normally be considered as low risk where it can be demonstrated that sewage effluent is hydrogeologically isolated from existing or potential supply aquifer(s).

Based on the observations made on the 9 test pits, the overburden can be described as shallow with the overburden thickness ranging from 0.15 m to greater than 1.98 m overlaying limestone bedrock. At most of the test pit locations the overburden thickness was 0.30 m or less. The overburden does not provide sufficient isolation.

The depth to first water found water as reported in the well records for the four Site wells ranged from 15.8 mbgs to 71.0 mbgs. It is noted that the surface of the limestone bedrock often exhibits weathering, but such weathering is thin (on the order of 0.2 m or less) with competent rock below. Based on the above observed conditions and the review of the MECP Well Record database it is concluded that, in general, the water-bearing features in aquifers targeted has on the order of greater than 15 m of bedrock isolating it from the surface. Usually, isolation is considered to be present if greater than 10 m of competent rock is present between ground surface and the water-bearing features. It is also noted that the use of tertiary treatment systems for wastewater treatment would provide considerable additional protection to the aquifer by reducing the effluent strength.

Step 2 of the assessment of potential for groundwater impact by on-Site sewage system is met and the assessment does not need to advance to Step 3.

The Site is suitable for in-ground wastewater disposal based on overburden character and Water Quality Impact Risk Assessment as per D-5-4.

6.1 Conclusions and Recommendations

- No municipal or communal servicing options are available to the location of the proposed development. Residential dwellings in the area are serviced by individual wells and in-ground wastewater treatment systems. Individual wells and in-ground wastewater treatment systems are a suitable servicing approach for the proposed development.

- Disinfection of the raw water supply from each well is recommended. This recommendation is most commonly addressed by a UV-system or chlorination with appropriate pre-filtration. Such systems are readily available.
- Hardness in the raw water can be expected to exceed the ODWQS operational guideline of 100-150 mg/L but is expected to be considerably below 500 mg/L and within a range that is easily treatable with a water softener. If the user finds the hard water unpalatable or has concerns on scale buildup, hardness can be easily treated with a water softener.
- With respect to in-ground wastewater disposal, the proposed lot sizes are suitable for the proposed development and provide sufficient space for a primary and alternative septic bed location for Class IV type systems. The areas required if tertiary wastewater treatment systems are used would be notably reduced.
- Class IV systems are suitable for the for the in-ground wastewater disposal. However, it is suggested that the client consider tertiary treatment systems which would provide enhanced wastewater treatment, require smaller bed sizes, and perhaps provide a cost saving based on less imported material being required.

Based on the findings of this Servicing Options Statement, Terrain Assessment and Hydrogeological Study in Support of Development

It is Pinchin's professional opinion that:

- Potable water and wastewater servicing is the most appropriate approach for servicing the proposed development;
- The water supply wells installed on the Site are capable of providing sufficient quantity of water for the proposed residential development;
- Water quality is good, but if the user finds the hardness or manganese to be unpalatable or problematic, then treatment by way of a simple water softener or filter systems may effectively address this condition. Sodium exceeded the 20 mg/L warning level at one of the wells. If sodium levels pose a dietary or medical concern, an undercounter reverse osmosis system connected to a dedicate drinking water spigot could be part of the water treatment system;
- No unacceptable adverse interference is expected to surrounding groundwater users from the proposed development;

- There is adequate space for Class IV in-ground wastewater disposal beds (primary and alternative) for all proposed lots;
- Overburden is generally thin on the Site and additional material would be required to be included meet OBC and Municipal design requirements for Class IV systems for some lots. Such considerations would be incorporated into the system design by the septic installer and is beyond the scope of this investigation; and
- The Site is suitable for the proposed development with respect to individual servicing for both potable water supply and wastewater disposal.

7.0 TERMS AND LIMITATIONS

This Servicing Options Statement, Terrain Assessment and Hydrogeological Study in Support of Development was performed for Douglas Landing Developments (Client) in order to fulfill the hydrogeological-related requirements as identified by the municipality.

Conclusions derived are specific to the immediate area of study and cannot be extrapolated extensively away from a sample location. Samples have been analyzed for a set of parameters as specified in the MECP Guideline D-5.

No environmental assessment can wholly eliminate uncertainty regarding the potential for recognized environmental conditions on a property. Performance of this Servicing Options Statement, Terrain Assessment and Hydrogeological Study in Support of Development is intended to reduce, but not eliminate, uncertainty regarding the potential for recognized environmental conditions on the Site.

This this Servicing Options Statement, Terrain Assessment and Hydrogeological Study in Support of Development was performed in general compliance with currently acceptable practices for environmental site investigations, and specific Client requests, as applicable to this Site.

This report was prepared for the exclusive use of the Client, subject to the terms, conditions and limitations contained within the duly authorized proposal for this project. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, is the sole responsibility of such third parties. Pinchin accepts no responsibility for damages suffered by any third party as a result of decisions made or actions conducted.

If additional parties require reliance on this report, written authorization from Pinchin will be required. Pinchin disclaims responsibility of consequential financial effects on transactions or property values, or requirements for follow-up actions and costs.

No other warranties are implied or expressed. Furthermore, this report should not be construed as legal advice. Pinchin will not provide results or information to any party unless disclosure by Pinchin is required by law.

Pinchin makes no other representations whatsoever, including those concerning the legal significance of its findings, or as to other legal matters touched on in this report, including, but not limited to, ownership of any property, or the application of any law to the facts set forth herein. With respect to regulatory compliance issues, regulatory statutes are subject to interpretation and these interpretations may change over time.

CLOSING REMARKS

We trust that the foregoing information is satisfactory for your present requirements.

Should you have any questions about the report or require additional information, please contact the Project Manager at 613.449.3731 or ptibble@pinchin.com.

Pinchin Ltd.

Prepared by:

PROFESSIONAL GEOSCIENTIST
PHILIP A. TIBBLE
PRACTISING MEMBER
1107
2025
ONTARIO

Phil Tibble, M.Sc., P.Geo., QPESA
Senior Technical Manager (Hydrogeology) • 613.449.3731
ptibble@pinchin.com

Reviewed by:

Byron O'Connor, P.Eng., QPESA
Senior Technical Manager
613.484.5607
boconnor@pinchin.com

Encl.: Appendix I - Figures
Appendix II - Tables
Appendix III - MECP Well Records
Appendix IV - Laboratory Certificates

\\pinchin.com\kgn\Job\283000s\0283258.001 GillianEspie,9243McArtonRd,Ott,ERC,Potab\Deliverables\Report\283258.001 Hydrogeo Study Report 9243McArtonRd Ottawa ESPIE.docx
Template: Groundwater Monitoring Report Template, EDR, July 23, 2024

APPENDIX I
Figures

PINCHIN

PROJECT NAME:	HYDROGEOLOGICAL STUDY AND TERRAIN ASSESSMENT
CLIENT NAME:	DOUGLAS LANDING DEVELOPMENTS
PROJECT LOCATION:	9243 MCARTON ROAD, BECKWITH TOWNSHIP, ONTARIO
FIGURE NAME:	KEY MAP
FIGURE NUMBER	1

PROJECT NUMBER:	SCALE:	DRAWN BY:	REVIEWED BY:	DATE:
283358.001	AS SHOWN	CF	PT	JANUARY 2025



LEGEND

- DOMESTIC MONITORING WELL
- BOREHOLE
- GROUNDWATER MONITORING WELL
- TEST PIT
- SITE FEATURES
- LOT PARCEL
- SITE BOUNDARY

NOTES:
1) Proprietary information may not be reproduced or divulged without prior written consent of Pinchin Ltd.
2) This drawing may have been reduced. All scale notations indicated are based on a 11"x17" format drawings.
3) Legend is color dependent. Non-colour copies may alter interpretation.
4) Coordinate system: NAD 1983 CSRS UTM Zone 18N.
5) Source: Pinchin Ltd., © OpenStreetMap (and) contributors, CC-BY-SA.

130 65 0 130
Metres

PINCHIN

PROJECT NAME
HYDROGEOLOGICAL STUDY AND TERRAIN ASSESSMENT

CLIENT NAME
DOUGLAS LANDING DEVELOPMENTS

PROJECT LOCATION
9243 MCARTON ROAD, BECKWITH TOWNSHIP, ONTARIO

FIGURE NAME
SITE PLAN WITH LAYOUT AND TESTING LOCATIONS

PROJECT NUMBER:	SCALE
283358.001	AS SHOWN
DRAWN BY: CF	REVIEWED BY: PT
DATE: JANUARY 2025	FIGURE NUMBER: 2



LEGEND

- MECP WELL
- SITE BOUNDARY
- 500M BUFFER

NOTES:
1) Proprietary information may not be reproduced or divulged without prior written consent of Pinchin Ltd.
2) This drawing may have been reduced. All scale notations indicated are based on a 11"x17" format drawings.
3) Legend is color dependent. Non-colour copies may alter interpretation.
4) Coordinate system: NAD 1983 CSRS UTM Zone 18N.
5) Source: Pinchin Ltd., © OpenStreetMap (and) contributors, CC-BY-SA.

PINCHIN

PROJECT NAME
HYDROGEOLOGICAL STUDY AND TERRAIN ASSESSMENT

CLIENT NAME
DOUGLAS LANDING DEVELOPMENTS

PROJECT LOCATION
9243 MCARTON ROAD, BECKWITH TOWNSHIP, ONTARIO

FIGURE NAME
MECP WELLS WITHIN 500M

PROJECT NUMBER:	SCALE
283358.001	AS SHOWN
DRAWN BY: CF	REVIEWED BY: PT
DATE: JANUARY 2025	FIGURE NUMBER: 3


Figure 4: Pumping Well #1 (A360958)
0.00
0.05
0.10
0.15
0.20
0.25
Drawdown (Metres)
0
60
120
180
240
300
360
420
480
540
600
Elapsed Time (Minutes)
Pump On
Pump Off
Drawdown


Figure 5: Pumping Well #2 (A360957)
Drawdown (Metres)
0.00
0.10
0.20
0.30
0.40
0.50
0.60
0
60
120
180
240
300
360
420
480
Elapsed Time (Minutes)
Pump On
Pump Off
Drawdown


Figure 6: Pumping Well #3 (A360960)
Drawdown (Metres)
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0
60
120
180
240
300
360
420
480
Elapsed Time (Minutes)
Pump On
Pump Off
Drawdown

Figure 7: Pumping Well #4 (A360959)




Figure 8a: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360957 (Well #1)
Drawdown (Metres)
-0.50
0.00
0.50
1.00
1.50
2.00
-360
-240
-120
0
120
240
360
480
600
720
Elapsed Time (Minutes)
Pump ON
Pump OFF
Well #2
Well #3
Well #4
244 Ridgemont
322 Ridgemont
270 Ridgemont
Pumping Well #1


Figure 8b:Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360957 (Well #1) Reduced Y-axis
Drawdown (Metres)
-0.05
0.00
0.05
0.10
0.15
0.20
-360
-240
-120
0
120
240
360
480
600
720
Elapsed Time (Minutes)
Pump ON
Pump OFF
Well #2
Well #3
Well #4
244 Ridgemont
322 Ridgemont
270 Ridgemont
Pumping Well #1

Figure 9a: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360957 (Well #2)



Figure 9b: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360957 (Well #2) Reduced Y-axis




Figure 10a: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360959 (Well #3)
Drawdown (Metres)
-0.5
0.0
0.5
1.0
1.5
2.0
2.5
3.0
3.5
-360
-240
-120
0
120
240
360
480
600
720
Elapsed Time (Minutes)
Pump ON
Pump OFF
Well #1
Well #2
Well #4
244 Ridgemont
322 Ridgemont
270 Ridgemont
Pumping Well #3


Figure 10b: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360959 (Well #3) Reduced Y-axis
Drawdown (Metres)
-0.02
0.00
0.02
0.04
0.06
0.08
-360
-240
-120
0
120
240
360
480
600
720
Elapsed Time (Minutes)
Pump ON
Pump OFF
Well #1
Well #2
Well #4
244 Ridgemont
322 Ridgemont
270 Ridgemont
Pumping Well #3


Figure 11a: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360959 (Well #4)
Drawdown (Metres)
-0.5
0.0
0.5
1.0
1.5
2.0
2.5
3.0
3.5
-360
-240
-120
0
120
240
360
480
600
720
Elapsed Time (Minutes)
Pump ON
Pump OFF
Well #1
Well #2
Well #3
244 Ridgemont
322 Ridgemont
270 Ridgemont
Pumping Well #4


Figure 11b: Water Level Drawdown and Recovery During Pumping Test
Pumping Well A360959 (Well #4) Reduced Y-axis
Drawdown (Metres)
-0.02
0.00
0.02
0.04
0.06
0.08
0.10
-360
-240
-120
0
120
240
360
480
600
720
Elapsed Time (Minutes)
Pump ON
Pump OFF
Well #1
Well #2
Well #3
244 Ridgemont
322 Ridgemont
270 Ridgemont
Pumping Well #4

APPENDIX II
Tables

TABLE 1

Summary of Supply Well Characteristics for Wells within ~500 m of the Site

Douglas Landing Developments

9243 McArton Road, Beckwith Township, Ontario

Well Record I.D.	Well Tag Number	Audit Number	Well Type	Well Depth (m)	Overburden Thickness (m)	Unit(s) Well Completed In	Recommended Pumping rate (LPM)	Date of Completion (yyyy-mm-dd)	Water Found at (m)		
3500537	N/A	N/A	Drilled	18.0	0.91	Limestone	45.5	1958-10-09	16.8		
3506860	N/A	N/A	Drilled	18.6	0.61	Shale	81.8	1984-06-14	16.5		
3508494	N/A	41124	Drilled	38.1	0.91	Sandstone	22.7	1988-09-02	36.6		
3508646	N/A	44884	Drilled	16.8	2.10	Limestone	36.4	1988-12-12	16.2		
3509344	N/A	73407	Drilled	15.8	2.40	Limestone	36.4	1990-05-30	15.8		
3509543	N/A	73442	Drilled	28.00	0.61	Limestone	136.4	1990-10-13	25.0	28.3	
3511611	N/A	153198	Drilled	37.5	0.61	Limestone	22.7	1995-10-30	34.1		
7183286	A127986	Z128553	Drilled	73.2	1.83	Limestone / Sandstone	90.9	2012-05-31	71.0		
7183288	A128058	Z128554	Drilled	55.2	0.91	Limestone / Sandstone	90.9	2012-05-08	52.1		
7183289	A128068	Z128555	Drilled	75.3	0.91	Limestone / Sandstone	90.9	2012-05-09	51.8	73.2	
7183290	A128066	Z128556	Drilled	55.2	1.22	Limestone / Sandstone	90.9	2012-05-09	50.3	52.4	
7183291	A128062	Z128557	Drilled	43.3	1.22	Limestone / Sandstone	90.9	2012-05-09	23.5	36.9	40.2
7268601	A195938	Z223093	Drilled	42.4	1.07	Limestone / Sandstone	45.5	2016-06-20	27.7	38.1	
7268602	A195941	Z223094	Drilled	30.5	0.91	Limestone / Sandstone	54.6	2016-06-21	27.1	30.2	
7268603	A195942	Z223095	Drilled	42.4	0.00	Limestone / Sandstone	27.8	2016-06-23	25.3	42.4	
7271813	A195956	Z223096	Drilled	42.4	0.00	Limestone / Sandstone	36.4	2016-09-06	42.4		
7279392	A195975	Z243269	Drilled	73.2	0.00	Limestone / Sandstone	68.2	2017-01-05	38.7	71.6	
7281316	A213224	Z243284	Drilled	39.6	2.10	Limestone	22.7	2017-01-31	35.8		
7288275	A213226	Z260669	Drilled	42.7	1.72	Limestone / Shale layers	40.9	2017-05-11	21.3	39.6	
7288276	A213245	Z260668	Drilled	42.7	1.22	Limestone	36.4	2017-05-12	39.3		
7288277	A213227	Z260670	Drilled	42.7	1.68	Limestone / Shale layers	54.6	2017-05-13	25.1	40.4	
7298154	A227986	Z260689	Drilled	42.7	1.37	Limestone / Shale layers	31.8	2017-10-10	24.4	42.7	
7298155	A227987	Z260700	Drilled	36.6	0.91	Limestone / Shale layers	45.5	2017-10-10	25.3	32.9	
7298156	A213255	Z260690	Drilled	36.6	1.98	Limestone / Shale layers	68.3	2017-09-29	19.2	28.0	
7308479	A228006	Z260717	Drilled	54.9	0.61	Limestone / Shale layers	68.3	2018-03-07	39.0	52.3	
7325842	A252424	Z292769	Drilled	54.9	0.61	Limestone / Shale layers	45.5	2018-12-10	25.3	36.6	
7325843	A252425	Z292768	Drilled	36.6	0.46	Limestone / Shale layers	54.6	2018-12-09	25.6	32.0	
7332598	A252405	Z292766	Drilled	61.0	0.00	Limestone	36.4	2019-04-15	23.8	56.1	
7349971	A276761	Z318977	Drilled	37.8	2.44	Limestone / Sandstone layers	45.5	2019-12-04	26.5	34.7	
7352342	A276752	Z318991	Drilled	30.2	1.37	Limestone / Shale layers	54.6	2019-12-19	25.8		
7352343	A276739	Z318976	Drilled	54.9	0.91	Limestone / Sandstone layers	36.4	2019-11-11	24.4	30.5	
7352438	A276753	Z318978	Drilled	48.8	1.22	Limestone	31.8	2019-12-10	20.7	33.2	45.1
7356155	A276774	Z334321	Drilled	36.6	0.00	Limestone / Sandstone layers	63.6	2020-03-12	25.3	32.9	
7363398	A296816	Z334345	Drilled	48.8	0.91	Limestone / Sandstone	68.2	2020-07-01	32.8	46.6	
7363399	A296814	Z334339	Drilled	48.8	1.22	Limestone / Sandstone layers	36.4	2020-07-02	23.5	29.9	42.1
7371206	A296837	Z349864	Drilled	54.9	1.83	Limestone	40.9	2020-09-30	27.1	48.8	
7384451	A309683	Z349898	Drilled	42.7	1.22	Limestone / Sandstone layers	40.9	2021-03-31	23.5	25.6	36.6
7384452	A309684	Z349906	Drilled	53.6	2.90	Limestone / Sandstone layers	36.4	2021-03-31	50.6		
7384453	A309682	Z349899	Drilled	30.5	1.52	Limestone / Sandstone layers	90.9	2021-03-31	20.4	28.0	
7390397	A309702	Z361794	Drilled	36.6	0.15	Limestone / Shale layers	54.6	2021-06-05	18.6	29.9	
Site Wells											
7451625	A360958	Z394524	Drilled	30.5	0.91	Limestone	90.9	2023-03-02	20.4	28.0	
7451628	A360957	Z394525	Drilled	42.7	0.91	Limestone	54,6	2023-03-02	40.5		
7451627	A360960	Z394526	Drilled	51.8	0.61	Limestone	90.9	2023-03-01	48.8	50.3	
7451626	A360959	Z394527	Drilled	54.9	0.61	Limestone	45.7	2023-02-28	23.5	52.7	

TABLE 8
RAW WELL WATER ANALYTICAL RESULTS
Douglas Landing Developments
9243 McArton Road, Beckwith Township, Ontario

Parameter	Units	MDL	ODWQS Standards		Sample Designation			
					Sample Collection Date (dd/mm/yyyy)			
			Standard	Type of Standard	Well #1 A360958	Well #2 A360957	Well #3 A360960	Well #4 A360959
					25-10-2024	24-10-2024	23-10-2024	21-10-2024
Microbiological Parameters								
E. Coli	CFU/100mL	1	0	MAC	0	0	0	0
Total Coliforms	CFU/100mL	1	0	MAC	0	0	0	0
General Inorganics								
Alkalinity, total	mg/L	5	30-500	OG	260	262	277	279
Ammonia as N	mg/L	0.01	-	-	0.2	0.2	0.13	<0.05
Dissolved Organic Carbon	mg/L	1	5	AO	1.8	1.7	2.4	1.5
Colour	TCU	2	5	AO	3	<2	<2	<2
Conductivity	uS/cm	1	-	-	672	636	737	781
Hardness	mg/L		500 / 80-100	AO / OG	**343**	**311**	**357**	**385**
pH	pH Units	0.1	6.5-8.5	OG	8.17	8.08	7.99	8.14
Total Dissolved Solids	mg/L	10	500	-	349	330	385	409
Turbidity	NTU	0.1	5	AO	2.0	2.5	1.2	0.5
Anions								
Chloride	mg/L	0.5	250	AO	19.9	23.3	39.3	49.8
Fluoride	mg/L	0.1	1.5	MAC	<0.1	<0.1	<0.1	<0.1
Nitrate as N	mg/L	0.1	10	MAC	<0.05	0.05	<0.05	1.08
Nitrite as N	mg/L	0.1	1	MAC	<0.05	<0.05	<0.05	<0.05
Sulphate	mg/L	1	500	AO	61	38	58	64
Metals								
Calcium	mg/L	0.02	-	-	90.8	74.8	84	94.4
Iron	mg/L	0.005	0.3	AO	0.131	0.214	0.10	0.027
Magnesium	mg/L	0.2	-	-	28.2	30.1	35.7	36.2
Manganese	mg/L	0.001	0.05	AO	**0.144**	0.009	0.008	0.007
Potassium	mg/L	0.1	-	-	8	4.2	3.9	3.1
Sodium	mg/L	0.2	20 / 200	*MAC** / AO	***39.8***	8.0	11.3	15

Notes:

Ontario Drinking Water Quality Standards

Type of Standard
MAC: Maximum Acceptable Concentration
AO: Aesthetic Objective
OG: Operational Guidelines

BOLD	Exceed MAC Standard
BOLD	Exceeds AO or OG Standard
BOLD	Reportable Detection Limit Exceeds Standard

* This health-related limit for sodium is a "warning level" only. Exceedance calls for a recommendation that the local Medical Officer of Health be notified in order to alert persons with relevant medical conditions. Sodium also has an Aesthetic Objective of 200 mg/L. Technical Support Document for Ontario Drinking Water Standards, Objectives and Guidelines June 2003 Revised June 2006 (PIBS 4449e01)

APPENDIX III
MECP Water Well Records

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

Tag#:A360957 (Print Below) — A360957

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	Dr. Gillian Espie		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
1 Forillion Crescent	Kanata	ON	K2M 2W5	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
(NO Civic) Ramsay Concession 12	Beckwith	P/L 25	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415351	5003544		TW#2 of 4

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	To
	Sand	+ Stones		0	3
Grey	+ Green Limestone			3	133
Grey	+ Green Limestone			133	140

TEST WELL # 2 of 4

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³)
40	30	Neat cement	10.92
30	0	Bentonite slurry	8.4

Method of Construction

☐ Cable Tool ☐ Diamond ☒ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☐ Air percussion ☐ Other, specify

Well Use

☐ Public ☒ Domestic ☐ Livestock ☐ Irrigation ☐ Industrial ☐ Other, specify ☐ Commercial ☐ Municipal ☐ Test Hole ☐ Cooling & Air Conditioning ☐ Not used ☐ Dewatering ☐ Monitoring

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6 1/4"	Steel	.188"	+2'	40'
6"	Open Hole		40'	140'

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth (m/ft)	Kind of Water: ☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
133	☒	0'	40'	9 3/4"
		40'	140'	6"

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	7681

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6059 Franktown Road	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Hanna, Jeremy

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
13632		2023 03 31 (Y Y Y Y M M D D)

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify **Not tested**

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 130

Pumping rate (l/min/GPM): 18

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 25.6

If flowing give rate (l/min/GPM):

Recommended pump depth (m/ft): 100'

Recommended pump rate (l/min/GPM): 15

Well production (l/min/GPM): 15

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Water Level (m/ft)	Recovery Time (min)	Water Level (m/ft)
Static Level	23'4"		25'6"
1	24.2	1	24.3
2	24.5	2	23.9
3	24.7	3	23.7
4	24.8	4	23.5
5	24.9	5	23.4
10	25.1	10	23.4
15	25.2	15	23.4
20	25.3	20	23.4
25	25.3	25	23.4
30	25.4	30	23.4
40	25.5	40	23.4
50	25.5	50	23.4
60	25.6	60	23.4

Map of Well Location

Please provide a map below following instructions on the back. N



Comments: 3/4HP-15GPM SSP@100FT

Well owner's information package delivered	Date Package Delivered	Ministry Use Only
☐ Yes ☐ No	2023 03 03	Audit No. Z394525
	2023 03 02	Received

0506E (2020/05) © Queen's Printer for Ontario, 2020 — Ministry's Copy

---

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

Tag#:A360958 (Print Below) — A360958

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	Dr. Gillian Espie		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
1 Forillion Crescent	Kanata	ON	K2M 2W5	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
(NO Civic) Ramsay Concession 12	Beckwith	P/L 25	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415424	5003394		Test well # 1 of 4

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	To
	Sand, Clay	[redacted]	+ Stones	0	3
Grey	+ Green Limestone			3	67
Grey	+ Green Limestone			67	92
Grey	+ Green Limestone			92	100

TEST WELL # 1 OF 4

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³)
40	30	Neat cement	10.92
30	0	Bentonite slurry	4.2

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☐ Air percussion ☐ Other, specify

Well Use

☐ Public ☒ Domestic ☐ Livestock ☐ Irrigation ☐ Industrial ☐ Other, specify ☐ Commercial ☐ Municipal ☐ Test Hole ☐ Cooling & Air Conditioning ☐ Not used ☐ Dewatering ☐ Monitoring

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6 1/4"	Steel	.188"	+2'	40'
6"	Open Hole		40'	100'

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth (m/ft)	Kind of Water: ☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
67	☒	0'	40'	9 3/4"
92	☒	40'	100'	6"

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	7681

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6059 Franktown Road	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Hanna, Jeremy

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
13632		2023 03 31 (Y Y Y Y M M D D)

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify **Not tested**

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 90

Pumping rate (l/min/GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 26

If flowing give rate (l/min/GPM): X

Recommended pump depth (m/ft): 90'

Recommended pump rate (l/min/GPM): 20

Well production (l/min/GPM): 20

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Water Level (m/ft)	Recovery Time (min)	Water Level (m/ft)
Static Level	25'4"		26'
1	25.6	1	25.6
2	25.6	2	25.5
3	25.6	3	25.4
4	25.7	4	25.4
5	25.7	5	25.4
10	25.8	10	25.4
15	25.8	15	25.4
20	25.9	20	25.4
25	25.9	25	25.4
30	25.9	30	25.4
40	26	40	25.4
50	26	50	25.4
60	26'	60	25.4

Map of Well Location

Please provide a map below following instructions on the back. N



Comments: 1HP-20GPM S&T @ 100FT

Well owner's information package delivered	Date Package Delivered	Ministry Use Only
☐ Yes ☐ No	2023 03 03	Audit No. Z394524
	2023 03 02	Received

0506E (2020/05) © Queen's Printer for Ontario, 2020 — Ministry's Copy

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

We Tag#:A360959 (nt Below) — A360959

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	Dr. Gillian Espie		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
1 Forillion Crescent	Kanata	ON	K2M 2W5	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
(NO Civic) Ramsay Concession 12	Beckwith	P/L 25	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3 18	415122	5003057		TW# 4 of 4

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	To
	Sand			0	2
Grey	Limestone			2	77
Grey	Limestone			77	173
Grey	Limestone			173	180

TEST WELL # 4 of 4

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/yd³)
40	30	Neat cement	10.92
30	0	Bentonite slurry	4.2

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☒ Domestic ☐ Livestock ☐ Irrigation ☐ Industrial ☐ Other, specify ☐ Commercial ☐ Municipal ☐ Test Hole ☐ Cooling & Air Conditioning ☐ Not used ☐ Dewatering ☐ Monitoring

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6 1/4"	Steel	.188"	+2	40
6"	Open Hole		40	180

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth (m/ft)	Kind of Water	Gas	Other, specify
77	☐ Fresh ☒ Untested	☐	
173	☐ Fresh ☒ Untested	☐	
	☐ Fresh ☐ Untested	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	40	9 3/4"
40	180	6"

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify Not tested

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 170

Pumping rate (l/min/GPM): 10

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 24.3"

If flowing give rate (l/min/GPM):

Recommended pump depth (m/ft): 140'

Recommended pump rate (l/min/GPM): 10

Well production (l/min/GPM): 10

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	185"			24.3
1		21.5	1	20.1
2		21.9	2	19.6
3		22.1	3	19.3
4		22.3	4	19.1
5		22.4	5	19
10		22.8	10	18.7
15		23.1	15	18.6
20		23.4	20	18.5
25		23.6	25	18.5
30		23.8	30	18.5
40		24	40	18.5
50		24.2	50	18.5
60		24.3	60	18.5

Map of Well Location

Please provide a map below following instructions on the back.



Comments: 1/2HP-10GPM Set@140 FT

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	7681

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Frankdown Road	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Hanna, Jeremy

Well Technician's Licence No. 13632 — Signature of Technician and/or Contractor — Date Submitted 2023 03 31 (Y Y Y Y M M D D)

Well owner's information package delivered: ☐ Yes ☐ No

Date Package Delivered: 2023 03 02 / 2023 02 28

Ministry Use Only — Audit No. Z394527 — Received

0506E (2020/06) © Queen's Printer for Ontario, 2020 — Ministry's Copy

---

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

W Tag#:A360960 (rint Below) — A360960

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	Dr. Gillian Espie		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
1 Forillion Crescent	Kanata	ON	K2M 2W5	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
(NO Civic) Ramsay Concession 12	Beckwith	P/L 25	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3 18	415121	5003273		TW# 3 of 4

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	To
	Sand			0	2
Grey	Limestone			2	160
Grey	Limestone			160	170

TEST WELL # 3 of 4

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/yd³)
40	30	Neat cement	10.92
30	0	Bentonite slurry	4.2

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☒ Domestic ☐ Livestock ☐ Irrigation ☐ Industrial ☐ Other, specify ☐ Commercial ☐ Municipal ☐ Test Hole ☐ Cooling & Air Conditioning ☐ Not used ☐ Dewatering ☐ Monitoring

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6 1/4"	Steel	.188"	+2	40
6"	Open Hole		40	170

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth (m/ft)	Kind of Water	Gas	Other, specify
160	☐ Fresh ☒ Untested	☐	
165	☐ Fresh ☒ Untested	☐	
	☐ Fresh ☐ Untested	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	40	9 3/4"
40	170	6"

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify Not tested

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 160

Pumping rate (l/min/GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 23.9"

If flowing give rate (l/min/GPM): X

Recommended pump depth (m/ft): 100'

Recommended pump rate (l/min/GPM): 20

Well production (l/min/GPM): 20

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	23.4"			23.9"
1		23.6	1	23.5
2		23.6	2	23.4
3		23.6	3	23.4
4		23.6	4	23.4
5		23.7	5	23.4
10		23.8	10	23.4
15		23.8	15	23.4
20		23.8	20	23.4
25		23.9	25	23.4
30		23.9	30	23.4
40		23.9	40	23.4
50		23.9	50	23.4
60		23.9	60	23.4

Map of Well Location

Please provide a map below following instructions on the back.

Comments: 1HP-20GPM Set@100 FT

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	7681

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Frankdown Road	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Hanna, Jeremy

Well Technician's Licence No. 13632 — Signature of Technician and/or Contractor — Date Submitted 2023 03 31 (Y Y Y Y M M D D)

Well owner's information package delivered: ☒ Yes ☐ No

Date Package Delivered: 2023 03 02 / 2023 03 01

Ministry Use Only — Audit No. Z394526 — Received

0506E (2020/06) © Queen's Printer for Ontario, 2020 — Ministry's Copy

31F1E

Ministry of the Environment
Ontario

The Ontario Water Resources Act

WATER WELL RECORD

3506860

1. PRINT ONLY IN SPACES PROVIDED
2. CHECK ☒ CORRECT BOX WHERE APPLICABLE

11 | MUNICIP 35002 | CON CON | 12

COUNTY OR DISTRICT	TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE	CON, BLOCK, TRACT, SURVEY, ETC.	LOT
[redacted]	BECKWITH	12	026

DATE COMPLETED DAY 13 MO 05 YR 84

[redacted] 03499 | 5 | 0450 | 5 | BASIN CODE 26

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET FROM	TO
Brown	Sand		Fine	0	2
Brown	Shail		Soft	2	61

MOE VE-17

31 0002608 | 00616178S

32

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
0054	3 ☒ SULPHUR

51 CASING & OPEN HOLE RECORD

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET FROM	TO
06	1 ☒ STEEL	188	0	0021
6 ¼				

SCREEN: SIZE(S) OF OPENING (SLOT NO.) | DIAMETER INCHES | LENGTH FEET | MATERIAL AND TYPE | DEPTH TO TOP OF SCREEN FEET

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET FROM | TO | MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.)

71 PUMPING TEST

PUMPING TEST METHOD: 1 ☐ PUMP 2 ☒ BAILER | PUMPING RATE 0020 GPM | DURATION OF PUMPING 01 HOURS 00 MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	15 MINUTES	30 MINUTES	45 MINUTES	60 MINUTES
015 FEET	048 FEET	018 FEET	015 FEET	FEET	FEET

WATER LEVELS DURING: 1 ☐ PUMPING 2 ☒ RECOVERY

IF FLOWING GIVE RATE ___ GPM | PUMP INTAKE SET AT ___ FEET | WATER AT END OF TEST: 1 ☒ CLEAR 2 ☐ CLOUDY

RECOMMENDED PUMP TYPE: ☐ SHALLOW ☒ DEEP | RECOMMENDED PUMP SETTING 050 FEET | RECOMMENDED PUMPING RATE 0018 GPM

FINAL STATUS OF WELL 1: 1 ☒ WATER SUPPLY; 2 ☐ OBSERVATION WELL; 3 ☐ TEST HOLE; 4 ☐ RECHARGE WELL; 5 ☐ ABANDONED, INSUFFICIENT SUPPLY; 6 ☐ ABANDONED, POOR QUALITY; 7 ☐ UNFINISHED

WATER USE 01: 1 ☒ DOMESTIC; 2 ☐ STOCK; 3 ☐ IRRIGATION; 4 ☐ INDUSTRIAL; ☐ OTHER; 5 ☐ COMMERCIAL; 6 ☐ MUNICIPAL; 7 ☐ PUBLIC SUPPLY; 8 ☐ COOLING OR AIR CONDITIONING; 9 ☐ NOT USED

METHOD OF DRILLING 1: 1 ☒ CABLE TOOL; 2 ☐ ROTARY (CONVENTIONAL); 3 ☐ ROTARY (REVERSE); 4 ☐ ROTARY (AIR); 5 ☐ AIR PERCUSSION; 6 ☐ BORING; 7 ☐ DIAMOND; 8 ☐ JETTING; 9 ☐ DRIVING

LOCATION OF WELL

IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE. INDICATE NORTH BY ARROW.



DRILLERS REMARKS

CONTRACTOR: NAME OF WELL CONTRACTOR BOYD CAMERON | LICENCE NUMBER 1567.
ADDRESS RR 2 CLAYTON ONT.
NAME OF DRILLER OR BORER | LICENCE NUMBER
SIGNATURE OF CONTRACTOR Boyd Cameron | SUBMISSION DATE DAY 14 MO 6 YR 84

OFFICE USE ONLY: DATA SOURCE 1 | CONTRACTOR 1567 | 020884 | DATE OF INSPECTION | INSPECTOR | REMARKS

CSS.ES

FORM NO. 0506-4-77 FORM 7

MINISTRY OF THE ENVIRONMENT COPY

UTM 18 Z 4 1 4 5 1 0 E
9 R 5 0 0 3 2 7 0 N
Elev. 9 R 0 4 4 0
Basin 784

31 F/1E

ONTARIO

35 No. 537

GROUND WATER BRANCH OCT 24 1958 ONTARIO WATER RESOURCES COMMISSION

The Water-well Drillers Act, 1954
Department of Mines

Water-Well Record

[redacted] ip, Village, Town or City BECKWITH.
[redacted] Village, Town or City)
[redacted] ddress ALMONTE

Date completed 7 (day) Oct. (month) 58 (year)

Pipe and Casing Record		Pumping Test	
Casing diameter(s)	6"	Static level	17
Length(s)	8'	Pumping rate	10 GPM.
Type of screen	—	Pumping level	25'
Length of screen		Duration of test	2 HR.

Well Log / **Water Record**

Overburden and Bedrock Record	From ft.	To ft.	Depth(s) at which water(s) found	No. of feet water rises	Kind of water (fresh, salty, or sulphur)
Top Soil	0	3	40		
B. LIME	3	59	55	38	FRESH.

For what purpose(s) is the water to be used? FARM.
Is water clear or cloudy? CLEAR.
Is well on upland, in valley, or on hillside? UPLAND.
Drilling firm C. GOODBERRY WELL DRILLING LTD
Address VERONA
Name of Driller H. McGEE
Address CLAYTON
Licence Number
I certify that the foregoing statements of fact are true.
Date Oct 9/58. H. McGee
Signature of Licensee

Location of Well

In diagram below show distances of well from road and lot line. Indicate north by arrow.



Form 5

CSS.SS

Ministry of the Environment
Ontario

The Ontario Water Resources Act
WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED
2. CHECK ☒ CORRECT BOX WHERE APPLICABLE

11 | 3508646 | MUNICIP. 35002 | CON. CON 11 | PL 27R-3KSts

COUNTY OR DISTRICT	TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE	CON., BLOCK, TRACT, SURVEY, ETC.	LOT
LANARK	BECKWITH	11	26

[redacted] RR 2 ASHTON — DATE COMPLETED: DAY 30 MO 11 YR 88

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET FROM	TO
BROWN	CLAY SAND	STONE'S	PACKED	0'	7'
GREY	LIMESTONE		HARD	7'	40'
BLACK	LIMESTONE		POROUS	40'	55'

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
53	☒ FRESH

51 CASING & OPEN HOLE RECORD

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET FROM	TO
6 1/4"	☒ STEEL	1.88	0'	22'
6"	OPEN HOLE		22'	55'

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET FROM	TO	MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.)
4	21	TYPE 10 PORTLAND

71 PUMPING TEST

- PUMPING TEST METHOD: ☒ BAILER
- PUMPING RATE: 10 GPM
- DURATION OF PUMPING: 2 HOURS
- STATIC LEVEL: 10 FEET
- WATER LEVEL END OF PUMPING: 25 FEET
- WATER LEVELS DURING: 15 MINUTES 25 FEET; 30 MINUTES 25 FEET; 45 MINUTES 25 FEET; 60 MINUTES 25 FEET
- WATER AT END OF TEST: ☒ CLOUDY
- RECOMMENDED PUMP TYPE: ☒ DEEP
- RECOMMENDED PUMP SETTING: 40 FEET
- RECOMMENDED PUMPING RATE: 8 GPM

FINAL STATUS OF WELL: ☒ WATER SUPPLY

WATER USE: ☒ DOMESTIC

METHOD OF CONSTRUCTION: ☒ CABLE TOOL

LOCATION OF WELL

IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE. INDICATE NORTH BY ARROW.



44884

DRILLERS REMARKS

CONTRACTOR
- NAME OF WELL CONTRACTOR: M. KAVANAGH & SON WELL ~~DRILLING~~
- WELL CONTRACTOR'S LICENCE NUMBER: 3142
- ADDRESS: RR 2 CARLETON PLACE
- NAME OF WELL TECHNICIAN: LONNY M'NEELY
- WELL TECHNICIAN'S LICENCE NUMBER: 88-194
- SIGNATURE OF TECHNICIAN/CONTRACTOR: Michael Kavanagh
- SUBMISSION DATE: DAY 12 MO 12 YR 88

OFFICE USE ONLY
- DATA SOURCE / CONTRACTOR: 3142
- DATE RECEIVED: JAN 12 1989
- REMARKS: WDE
- CSS.ES

MINISTRY OF THE ENVIRONMENT COPY

FORM NO. 0506 (11/86) FORM 9

Ministry of the Environment
Ontario

The Ontario Water Resources Act
WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED
2. CHECK ☒ CORRECT BOX WHERE APPLICABLE

11 | 3508494 | MUNICIP. 35002 | CON. Part

COUNTY OR DISTRICT	TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE	CON., BLOCK, TRACT, SURVEY, ETC.	LOT
Lanark	Beckwith	12	26

OWNER (SURNAME FIRST): [redacted]

ADDRESS: 1060 Apolwdor Ave. Apt 2 Ottawa K1H 8A9 — DATE COMPLETED: DAY 1 MO 9 YR 88

21

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET FROM	TO
	clay			0'	3'
black & green	sandstone			3'	30'
gray	sandstone			30'	83'
gray	sandstone			83'	125'

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
120'	☒ FRESH

51 CASING & OPEN HOLE RECORD

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET FROM	TO
6"	☒ STEEL	188	0'	22'

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET FROM	TO	MATERIAL AND TYPE (CEMENT GROUT, LEAD PACKER, ETC.)
0	22	cement

71 PUMPING TEST

- PUMPING TEST METHOD: air ☒ PUMP
- PUMPING RATE: 5 GPM
- DURATION OF PUMPING: 30 MINS
- STATIC LEVEL: 28 FEET
- WATER LEVELS DURING: ☒ RECOVERY; 60 MINUTES 32 FEET
- PUMP INTAKE SET AT: 125' FEET
- WATER AT END OF TEST: ☒ CLEAR
- RECOMMENDED PUMP TYPE: ☒ DEEP
- RECOMMENDED PUMP SETTING: 105' FEET
- RECOMMENDED PUMPING RATE: 5 GPM

FINAL STATUS OF WELL: ☒ WATER SUPPLY

WATER USE: ☒ DOMESTIC

METHOD OF CONSTRUCTION: ☒ ROTARY (AIR)

LOCATION OF WELL

IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE. INDICATE NORTH BY ARROW.



41124

DRILLERS REMARKS

CONTRACTOR
- NAME OF WELL CONTRACTOR: Guy Hall Ltd
- WELL CONTRACTOR'S LICENCE NUMBER: 2558
- ADDRESS: McDonalds Corners Ont.
- NAME OF WELL TECHNICIAN: Earl Gemmill
- WELL TECHNICIAN'S LICENCE NUMBER: T0050
- SIGNATURE OF TECHNICIAN/CONTRACTOR: Guy Hall
- SUBMISSION DATE: DAY 2 MO 9 YR 88

OFFICE USE ONLY
- DATA SOURCE / CONTRACTOR: 2558
- DATE RECEIVED: OCT 21 1988
- CSS.ES

MINISTRY OF THE ENVIRONMENT COPY

FORM NO. 0506 (11/86) FORM 9

Ministry of the Environment
Ontario

The Ontario Water Resources Act

WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED
2. CHECK ☒ CORRECT BOX WHERE APPLICABLE

11 — 3509543 — MUNICIP 3502 — CON CON. — 11.2

COUNTY OR DISTRICT: LANARK — TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: BECKWITH — CON: 12 — BLOCK, TRACT, SURVEY, ETC: — LOT: 26

[redacted] R#3 CARP ONT. KOA 1L0 — DATE COMPLETED: DAY 9? MO 10 YR 90

RC: — ELEVATION: — RC: — BASIN CODE:

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET FROM	DEPTH - FEET TO
BROWN	EARTH		LOOSE	0'	2'
GREY	LIMESTONE		HARD	2'	40'
GREY/BLACK	LIMESTONE	SHALE	POROUS	40'	95'

31 — 32

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
82	1 ☒ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
93	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS

51 CASING & OPEN HOLE RECORD

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET FROM	DEPTH - FEET TO
6¼"	1 ☒ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC	1.88	0'	22'
6"	1 ☐ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC		22'	95'
	1 ☐ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC			
	1 ☐ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC			

SCREEN

SIZE-S OF OPENING (SLOT NO.) — DIAMETER — LENGTH
MATERIAL AND TYPE — DEPTH TO TOP OF SCREEN

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET FROM	TO	MATERIAL AND TYPE (CEMENT GROUT LEAD PACKER ETC.)
0	21	TYPE 10 PORTLAND

71 PUMPING TEST

PUMPING TEST METHOD: 1 ☐ PUMP 2 ☒ BAILER — PUMPING RATE: 30 GPM — DURATION OF PUMPING: 1 HOURS 30 MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	WATER LEVELS DURING: 15 MINUTES	30 MINUTES	45 MINUTES	60 MINUTES
25 FEET	45 FEET	45 FEET	45 FEET	45 FEET	45 FEET

1 ☐ PUMPING 2 ☐ RECOVERY

IF FLOWING GIVE RATE: — GPM — PUMP INTAKE SET AT: — FEET — WATER AT END OF TEST: 1 ☐ CLEAR 2 ☒ CLOUDY

RECOMMENDED PUMP TYPE: ☐ SHALLOW ☒ DEEP — RECOMMENDED PUMP SETTING: 60 FEET — RECOMMENDED PUMPING RATE: 8 GPM

LOCATION OF WELL

IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE. INDICATE NORTH BY ARROW.



DRILLERS REMARKS: 73442

FINAL STATUS OF WELL

1 ☒ WATER SUPPLY — 2 ☐ OBSERVATION WELL — 3 ☐ TEST HOLE — 4 ☐ RECHARGE WELL — 5 ☐ ABANDONED, INSUFFICIENT SUPPLY — 6 ☐ ABANDONED, POOR QUALITY — 7 ☐ UNFINISHED — ☐ DEWATERING

WATER USE

1 ☒ DOMESTIC — 2 ☐ STOCK — 3 ☐ IRRIGATION — 4 ☐ INDUSTRIAL — ☐ OTHER — 5 ☐ COMMERCIAL — 6 ☐ MUNICIPAL — 7 ☐ PUBLIC SUPPLY — 8 ☐ COOLING OR AIR CONDITIONING — 9 ☐ NOT USED

METHOD OF CONSTRUCTION

1 ☒ CABLE TOOL — 2 ☐ ROTARY (CONVENTIONAL) — 3 ☐ ROTARY (REVERSE) — 4 ☐ ROTARY (AIR) — 5 ☐ AIR PERCUSSION — 6 ☐ BORING — 7 ☐ DIAMOND — 8 ☐ JETTING — 9 ☐ DRIVING — ☐ DIGGING — ☐ OTHER

CONTRACTOR

NAME OF WELL CONTRACTOR: M. KAVANAGH & SON WELL DRILLING — WELL CONTRACTOR'S LICENCE NUMBER: 3142
ADDRESS: RR2 CARLETON PLACE
NAME OF WELL TECHNICIAN: MIKE KAVANAGH — WELL TECHNICIAN'S LICENCE NUMBER: T-0194
SIGNATURE OF TECHNICIAN/CONTRACTOR: M Kavanagh — SUBMISSION DATE: DAY 13 MO 10 YR 90

OFFICE USE ONLY

DATA SOURCE — CONTRACTOR: 3142 — DATE RECEIVED: NOV 01 1990
DATE OF INSPECTION — INSPECTOR
REMARKS: CSS.ES

MINISTRY OF THE ENVIRONMENT COPY

FORM NO. 0506 (11/86) FORM 9

Ministry of the Environment
Ontario

The Ontario Water Resources Act

WATER WELL RECORD

1. PRINT ONLY IN SPACES PROVIDED
2. CHECK ☒ CORRECT BOX WHERE APPLICABLE

11 — 3509344 — MUNICIP 3502 — CON CON. — Pt Lot 11

COUNTY OR DISTRICT: LANARK — TOWNSHIP, BOROUGH, CITY, TOWN, VILLAGE: BECKWITH — CON: — BLOCK, TRACT, SURVEY, ETC: 11 — LOT: 26

[redacted] RR 4 ALMONTE, ONT. — DATE COMPLETED: DAY 29 MO 5 YR 90

RC: — ELEVATION: — RC: — BASIN CODE:

LOG OF OVERBURDEN AND BEDROCK MATERIALS (SEE INSTRUCTIONS)

GENERAL COLOUR	MOST COMMON MATERIAL	OTHER MATERIALS	GENERAL DESCRIPTION	DEPTH - FEET FROM	DEPTH - FEET TO
BROWN	FILL	SAND, STONES	PACKED	0'	8'
GREY	LIMESTONE		HARD	8'	52'

31 — 32

41 WATER RECORD

WATER FOUND AT - FEET	KIND OF WATER
52	1 ☒ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS
	1 ☐ FRESH 2 ☐ SALTY — 3 ☐ SULPHUR 4 ☐ MINERALS 5 ☐ GAS

51 CASING & OPEN HOLE RECORD

INSIDE DIAM INCHES	MATERIAL	WALL THICKNESS INCHES	DEPTH - FEET FROM	DEPTH - FEET TO
6¼"	1 ☒ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC	1.88	0'	22'
6"	1 ☐ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☒ OPEN HOLE 5 ☐ PLASTIC		22'	52'
	1 ☐ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC			
	1 ☐ STEEL 2 ☐ GALVANIZED 3 ☐ CONCRETE 4 ☐ OPEN HOLE 5 ☐ PLASTIC			

SCREEN

SIZE-S OF OPENING (SLOT NO.) — DIAMETER — LENGTH
MATERIAL AND TYPE — DEPTH TO TOP OF SCREEN

61 PLUGGING & SEALING RECORD

DEPTH SET AT - FEET FROM	TO	MATERIAL AND TYPE (CEMENT GROUT LEAD PACKER ETC.)
6	21	TYPE 10 PORTLAND

71 PUMPING TEST

PUMPING TEST METHOD: 1 ☐ PUMP 2 ☒ BAILER — PUMPING RATE: — GPM — DURATION OF PUMPING: — HOURS — MINS

STATIC LEVEL	WATER LEVEL END OF PUMPING	WATER LEVELS DURING: 15 MINUTES	30 MINUTES	45 MINUTES	60 MINUTES
10 FEET	30 FEET	30 FEET	30 FEET	30 FEET	30 FEET

1 ☐ PUMPING 2 ☐ RECOVERY

IF FLOWING GIVE RATE: — GPM — PUMP INTAKE SET AT: — FEET — WATER AT END OF TEST: 1 ☐ CLEAR 2 ☒ CLOUDY

RECOMMENDED PUMP TYPE: ☐ SHALLOW ☒ DEEP — RECOMMENDED PUMP SETTING: 40 FEET — RECOMMENDED PUMPING RATE: 8 GPM

LOCATION OF WELL

IN DIAGRAM BELOW SHOW DISTANCES OF WELL FROM ROAD AND LOT LINE. INDICATE NORTH BY ARROW.



DRILLERS REMARKS: 73407

FINAL STATUS OF WELL

1 ☒ WATER SUPPLY — 2 ☐ OBSERVATION WELL — 3 ☐ TEST HOLE — 4 ☐ RECHARGE WELL — 5 ☐ ABANDONED, INSUFFICIENT SUPPLY — 6 ☐ ABANDONED, POOR QUALITY — 7 ☐ UNFINISHED — ☐ DEWATERING

WATER USE

1 ☒ DOMESTIC — 2 ☐ STOCK — 3 ☐ IRRIGATION — 4 ☐ INDUSTRIAL — ☐ OTHER — 5 ☐ COMMERCIAL — 6 ☐ MUNICIPAL — 7 ☐ PUBLIC SUPPLY — 8 ☐ COOLING OR AIR CONDITIONING — 9 ☐ NOT USED

METHOD OF CONSTRUCTION

1 ☒ CABLE TOOL — 2 ☐ ROTARY (CONVENTIONAL) — 3 ☐ ROTARY (REVERSE) — 4 ☐ ROTARY (AIR) — 5 ☐ AIR PERCUSSION — 6 ☐ BORING — 7 ☐ DIAMOND — 8 ☐ JETTING — 9 ☐ DRIVING — ☐ DIGGING — ☐ OTHER

CONTRACTOR

NAME OF WELL CONTRACTOR: M. KAVANAGH & SON WELL DRILLING — WELL CONTRACTOR'S LICENCE NUMBER: 3142
ADDRESS: RR 2 CARLETON PLACE
NAME OF WELL TECHNICIAN: LONNY McNEELY — WELL TECHNICIAN'S LICENCE NUMBER: 89-194
SIGNATURE OF TECHNICIAN/CONTRACTOR: M Kavanagh — SUBMISSION DATE: DAY 30 MO 5 YR 90

OFFICE USE ONLY

DATA SOURCE — CONTRACTOR: 3142 — DATE RECEIVED: JUN 06 1990
DATE OF INSPECTION — INSPECTOR
REMARKS: CSS.ES

MINISTRY OF THE ENVIRONMENT COPY

FORM NO. 0506 (11/86) FORM 9

Ontario — Ministry of the Environment

Tag#: A127986 (Print Below)

A127986

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	McArton Road Co-Tenancy		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
9094 Cavanagh Road	Ashton	ON	K0A 1B0	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
9153 McArton Road	Beckwith	P/L 6	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415241	5004058		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
	Sand	&	Boulders	0	6
Green & Grey	Limestone			6	233
Green & Grey	Limestone			233	240

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/yd³)
60	0	Neat cement	65.5

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Jetting ☐ Rotary (Conventional) ☐ Driving ☐ Rotary (Reverse) ☐ Digging ☐ Boring ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6"	Steel	188"	+2'	60'
5 7/8"	Open Hole		60'	240'

Status of Well

☒ Water Supply ☐ Replacement Well ☒ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth (m/ft)	Kind of Water	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
233'	☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify	0'	60'	6"
	☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify	60'	240'	5 7/8"
	☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify			

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	1119

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Franktown Road, RR#1	Richmond	ON	K0A 2Z0	sir-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)	Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
6138882170	Purcell, Shannon	T2122		2012 05 31

0506E (2007/12) © Queen's Printer for Ontario, 2007

Ministry's Copy

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify — Not tested

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 200

Pumping rate (l/min / GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 28.6

If flowing give rate (l/min / GPM): X

Recommended pump depth (m/ft): 100' (3/4HP-15gpm)

Recommended pump rate (l/min / GPM): 20

Well production (l/min / GPM): 20

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	28.1'		28.6'
1	28.6	1	28.1
2	28.6	2	28.1
3	28.6	3	28.1
4	28.6	4	28.1
5	28.6	5	28.1
10	28.6	10	28.1
15	28.6	15	28.1
20	28.6	20	28.1
25	28.6	25	28.1
30	28.6	30	28.1
40	28.6	40	28.1
50	28.6	50	28.1
60	28.6	60	28.1

Map of Well Location

Please provide a map below following instructions on the back.



Comments: TEST WELL #2 (3/4HP-15gpm Set @ 100ft)

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2012 05 14	2012 05 08

Ministry Use Only

Audit No. Z128553

Received MAY 29 2012

Ministry of Environment and Energy — Ontario

The Ontario Water Resources Act
WATER WELL RECORD

Print only in spaces provided.
Mark correct box with a checkmark, where applicable.

11 — 3511611 — Municipality 35902 — Con. CON — 12

County or District	Township/Borough/City/Town/Village	Con	block	tract	survey, etc.	Lot
Lanark	Beckwith		12			26

Owner's surname	First name	Address	Date completed
Neilcorp General Contracting Ltd		R.R. #1, Ramsay Meadows Carleton Place, Ontario K7C 3P1	27 10 month 95 year

Zone — Easting — Northing — HC — Elevation — RC — Basin Code

LOG OF OVERBURDEN AND BEDROCK MATERIALS (see instructions)

General colour	Most common material	Other materials	General description	Depth – feet From	To
Brown	Sandy Clay		Wet	0	2
Gray	Limestone		Hard	2	123

WATER RECORD

Water found at – feet	Kind of water
112	☐ Fresh ☐ Salty ☐ Sulphur ☐ Minerals ☐ Gas
NOT TESTED	☐ Fresh ☐ Salty ☐ Sulphur ☐ Minerals ☐ Gas
	☐ Fresh ☐ Salty ☐ Sulphur ☐ Minerals ☐ Gas
	☐ Fresh ☐ Salty ☐ Sulphur ☐ Minerals ☐ Gas
	☐ Fresh ☐ Salty ☐ Sulphur ☐ Minerals ☐ Gas

CASING & OPEN HOLE RECORD

Inside diam inches	Material	Wall thickness inches	Depth – feet From	To
6 1/4	☒ Steel ☐ Galvanized ☐ Concrete ☐ Open hole ☐ Plastic	.188	0	41
6 1/8	☐ Steel ☐ Galvanized ☐ Concrete ☒ Open hole ☐ Plastic		41	123
	☐ Steel ☐ Galvanized ☐ Concrete ☐ Open hole ☐ Plastic			

SCREEN

Sizes of opening (Slot No.)	Diameter inches	Length feet

Material and type — Depth at top of screen feet

PLUGGING & SEALING RECORD

☐ Annular space ☐ Abandonment

Depth set at – feet From	To	Material and type (Cement grout, bentonite, etc.)
39'6"	0	Groutefd Cement (5)

PUMPING TEST

Pumping test method	Pumping rate	Duration of pumping
☒ Pump ☐ Bailer	12 GPM	1 Hours Mins

Static level	Water level end of pumping	Water levels during	15 minutes	30 minutes	45 minutes	60 minutes
31 feet	60 feet	☒ Pumping ☐ Recovery	120 feet	100 feet	75 feet	60 feet

If flowing give rate	Pump intake set at	Water at end of test
GPM	feet	☐ Clear ☒ Cloudy

Recommended pump type	Recommended pump setting	Recommended pump rate
☐ Shallow ☒ Deep	75 feet	5 GPM

LOCATION OF WELL

In diagram below show distances of well from road and lot line. Indicate north by arrow.



153198

FINAL STATUS OF WELL

☒ Water supply ☐ Observation well ☐ Test hole ☐ Recharge well ☐ Abandoned, insufficient supply ☐ Abandoned, poor quality ☐ Abandoned (Other) ☐ Dewatering ☐ Unfinished ☐ Replacement well

WATER USE

☒ Domestic ☐ Stock ☐ Irrigation ☐ Industrial ☐ Commercial ☐ Municipal ☐ Public supply ☐ Cooling & air conditioning ☐ Not used ☐ Other

METHOD OF CONSTRUCTION

☐ Cable tool ☐ Rotary (conventional) ☐ Rotary (reverse) ☐ Rotary (air) ☒ Air percussion ☐ Boring ☐ Diamond ☐ Jetting ☐ Driving ☐ Digging ☐ Other

Name of Well Contractor	Well Contractor's Licence No.
Capital Water Supply Ltd.	1558

Address	Well Technician's Licence No.
P.O. Box 490 Stittsville, Ontario K2S 1A6	T0097

Name of Well Technician	Signature of Technician/Contractor	Submission date
S. Miller		day 30 mo 10 yr 95

MINISTRY USE ONLY: 1558 NOV 07 1995

CSS.ES

0506 (07/94) Front Form 9

2 - MINISTRY OF ENVIRONMENT & ENERGY COPY

Ontario — Ministry of the Environment

Well Record

Regulation 903 Ontario Water Resources Act

Tag#: A128068

A128068

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	McArton Road Co-Tenancy		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
9094 Cavanagh Road	Ashton	ON	K0A 1B0	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
9153 McArton Road	Beckwith	P/L 6	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415451	5003819		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
	Clay			0	3
Grey	Limestone			3	170
Grey	Limestone			170	216
Grey	Limestone	& Sand Stone		216	240
Grey	Limestone	& Sand Stone		240	247

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
60	0	Neat cement	25

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6"	Steel	.188"	+2	60
6"	Open Hole		60	247

Status of Well

☒ Water Supply
☐ Replacement Well
☒ Test Hole #4
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Gas	Other, specify
170 (m/ft)	☐ Fresh ☒ Untested	☐	
240 (m/ft)	☐ Fresh ☒ Untested	☐	
(m/ft)	☐ Fresh ☐ Untested	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	247	6"

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify **Not tested**

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 230

Pumping rate (l/min / GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 35.1

If flowing give rate (l/min / GPM): X

Recommended pump depth (m/ft): 100 (3/4HP - 15GPM)

Recommended pump rate (l/min / GPM): 20

Well production (l/min / GPM): 20

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	34.6		35.1
1	35	1	34.6
2	35	2	34.6
3	35	3	34.6
4	35	4	34.6
5	35	5	34.6
10	35	10	34.6
15	35	15	34.6
20	35	20	34.6
25	35.1	25	35.6
30	35.1	30	34.6
40	35.1	40	34.6
50	35.1	50	34.6
60	35.1	60	34.6

Map of Well Location

Please provide a map below following instructions on the back.



Comments: TEST WELL #4 (3/4 HP - 15GPM Set @ 100ft)

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	1119

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Franktown Road, RR#1	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Purcell, Shannon

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T2122		2012 05 31

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2012 05 14	2012 05 09

Ministry Use Only

Audit No. Z128555

Received JUN 29 2012

0506E (2007/12) © Queen's Printer for Ontario, 2007

Ministry's Copy

Ontario — Ministry of the Environment

Well Record

Regulation 903 Ontario Water Resources Act

Tag#: A128058

A128058

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	McArton Road Co-Tenancy		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
9094 Cavanagh Road	Ashton	ON	K0A 1B0	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
9153 McArton Road	Beckwith	P/L 6	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415282	5003874		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
	Sand			0	3
Grey	Limestone			3	171
Grey	Limestone			171	181

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
60	0	Neat cement	23.4

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6"	Steel	.188"	+2	60
5⅞"	Open Hole		60	181

Status of Well

☒ Water Supply
☐ Replacement Well
☒ Test Hole #3
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Gas	Other, specify
171 (m/ft)	☐ Fresh ☒ Untested	☐	
(m/ft)	☐ Fresh ☐ Untested	☐	
(m/ft)	☐ Fresh ☐ Untested	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	60	6"
60	181	5⅞"

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify **Not tested**

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 160

Pumping rate (l/min / GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 29.7

If flowing give rate (l/min / GPM): X

Recommended pump depth (m/ft): 100 (3/4HP - 15GPM)

Recommended pump rate (l/min / GPM): 20

Well production (l/min / GPM): 20

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	29.5		29.7
1	29.6	1	29.5
2	29.6	2	29.5
3	29.6	3	29.5
4	29.6	4	29.5
5	29.6	5	29.5
10	29.6	10	29.5
15	29.7	15	29.5
20	29.7	20	29.5
25	29.7	25	29.5
30	29.7	30	29.5
40	29.7	40	29.5
50	29.7	50	29.5
60	29.7	60	29.5

Map of Well Location

Please provide a map below following instructions on the back.



Comments: TEST WELL #3 (3/4 HP - 15GPM Set @ 100ft)

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	1119

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Franktown Road, RR#1	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Hanna, Jeremy

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T3632		2012 05 31

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2012 05 14	2012 05 09

Ministry Use Only

Audit No. Z128554

Received JUN 29 2012

0506E (2007/12) © Queen's Printer for Ontario, 2007

Ministry's Copy

Well Record

Ontario — Ministry of the Environment

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Tag#: A128062 (Print Below) — A128062

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	McArton Road Co-Tenancy		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
9094 Cavanagh Road	Ashton	ON	K0A 1B0	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
9153 McArton Road	Beckwith	P/L 6	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415610	5003588		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
	Clay			0	4
Grey + Green	Limestone			4	77
Grey & Green	Limestone			77	121
Grey & Green	Limestone			121	132
Grey & Green	Limestone			132	142

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
60	0	Neat cement	21.8

Method of Construction

☐ Cable Tool ☐ Diamond ☒ Air percussion
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6	Steel	.188	+2	60
6	Open Hole		60	142

Status of Well

☒ Water Supply
☐ Replacement Well
☒ Test Hole #6
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth (m/ft)	Kind of Water	Gas	Other, specify
77	☐ Fresh ☒ Untested	☐	
121	☐ Fresh ☒ Untested	☐	
132	☐ Fresh ☒ Untested	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	142	6

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify **Not tested**

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 120

Pumping rate (l/min / GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 36.2

If flowing give rate (l/min / GPM): X

Recommended pump depth (m/ft): 100' (3/4HP - 15gpm)

Recommended pump rate (l/min / GPM): 20

Well production (l/min / GPM): 20

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	35		36.2
1	36	1	35
2	36	2	35
3	36.1	3	35
4	36.1	4	35
5	36.1	5	35
10	36.1	10	35
15	36.1	15	35
20	36.1	20	35
25	36.1	25	35
30	36.2	30	35
40	36.2	40	35
50	36.2	50	35
60	36.2	60	35

Map of Well Location

Please provde a map below following instructions on the back.



Comments: TEST WELL #6 (3/4HP-15gpm set @ 100ft)

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	1118

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Franktown Road, RR#1	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Purcell, Shannon

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T2122		2012 05 31

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2012 5 14	2012 05 09

Ministry Use Only

Audit No. Z 128557

Received JUN 29 2012

0506E (2007/12) © Queen's Printer for Ontario, 2007

Ministry's Copy

Ontario — Ministry of the Environment

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Page ____ of ____

Tag#: A128066 (Print Below) — A128066

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	McArton Road Co-Tenancy		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
9094 Cavanagh Road	Ashton	ON	K0A 1B0	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
9153 McArton Road	Beckwith	P/L 6	12

County/District/Municipality	City/Town/Village	Province	Postal Code
Lanark	Ashton	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415465	5003648		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
	Sand	Clay		0	4
Grey & Green	Limestone			4	165
Grey & Green	Limestone			165	172
Grey & Green	Limestone			172	181

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
60	0	Neat cement	18.7

Method of Construction

☐ Cable Tool ☐ Diamond ☒ Air percussion
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6	Steel	.188	+2	60
5⅞	Open Hole		60	181

Status of Well

☒ Water Supply
☐ Replacement Well
☒ Test Hole #5
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth (m/ft)	Kind of Water	Gas	Other, specify
165	☐ Fresh ☒ Untested	☐	
172	☐ Fresh ☒ Untested	☐	
	☐ Fresh ☐ Untested	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	60	6
60	181	5⅞

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify **Not tested**

If pumping discontinued, give reason: X

Pump intake set at (m/ft): 160

Pumping rate (l/min / GPM): 20

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 35.2

If flowing give rate (l/min / GPM): X

Recommended pump depth (m/ft): 100' (3/4HP - 15gpm)

Recommended pump rate (l/min / GPM): 20

Well production (l/min / GPM): 20

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	34.8		35.2
1	35.1	1	34.8
2	35.1	2	34.8
3	35.1	3	34.8
4	35.1	4	34.8
5	35.1	5	34.8
10	35.1	10	34.8
15	35.1	15	34.8
20	35.1	20	34.8
25	35.1	25	34.8
30	35.2	30	34.8
40	35.2	40	34.8
50	35.2	50	34.8
60	35.2	60	34.8

Map of Well Location

Please provide a map below following instructions on the back.



Comments: TEST WELL #5 (3/4HP-15gpm set @ 100ft)

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
Air Rock Drilling Co. Ltd.	1118

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
6659 Franktown Road, RR#1	Richmond	ON	K0A 2Z0	air-rock@sympatico.ca

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6138382170	Hanna, Jeremy

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T3632		2012 05 31

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☐ Yes ☐ No	2012 05 14	2012 05 09

Ministry Use Only

Audit No. Z 128556

Received JUN 29 2012

0506E (2007/12) © Queen's Printer for Ontario, 2007

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A195941

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT ARGUE DR.	STITTSVILLE	ONT.	K7S2H2	6132235184

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
162 RIDGEMONT DR.	BECKWITH	5	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415141	5004020		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY		FILL	0	3
BROWN	SHALE			3	4
GREY	LIMESTONE	GREY SANDSTONE		4	100

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³ / yd³)
0	63½	BENTONITE GROUT	.960

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0+2	63½

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Depth To	Diameter (cm/in)
89 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	63½	100	6"
99 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested			
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 95

Pumping rate (l/min / GPM): 10

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 30.05

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 90

Recommended pump rate (l/min / GPM): 12

Well production (l/min / GPM): 12

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	22.31		
1	27.02	1	23.16
2	27.23	2	22.35
3	28.04	3	22.31
4	28.56	4	
5	28.87	5	
10	29.45	10	
15	29.60	15	
20	29.60	20	
25	29.76	25	
30	29.80	30	
40	29.95	40	
50	30.0	50	
60	30.05	60	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	20160621	20160621

Ministry Use Only

Audit No. Z223094

Received AUG 12 2016

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T517	Troy Saunders	20160721

0506E (2014/11) — Ministry's Copy — © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A195938

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G ARGUE DR	STITTSVILLE	ONT.	K7S2H2	6132235184

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
154 RIDGEMONT DR.	BECKWITH	4	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415255	5004073		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	SAND	BROKEN ROCK	FILL	0	3½
GREY	LIMESTONE			3½	60
GREY	LIMESTONE	LAYERS OF GREY SANDSTONE		60	139

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³ / yd³)
0	50	BENTONITE GROUT	.576
50	60	CEMENT GROUT	.110

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Materia (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0+3	60

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Depth To	Diameter (cm/in)
91 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	60	139	6"
125 (m/ft) ☐ Gas ☐ Other, specify HYDRO FRAC	☐ Fresh ☒ Untested			
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 129

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 20.16

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 129

Recommended pump rate (l/min / GPM): 10

Well production (l/min / GPM): 10

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	16.42		
1	19.80	1	19.85
2	19.83	2	16.42
3	19.85	3	
4	20.0	4	
5	20.2	5	
10	20.05	10	
15	20.07	15	
20	20.13	20	
25	20.14	25	
30	20.14	30	
40	20.15	40	
50	20.16	50	
60	20.16	60	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	20160620	20160820

Ministry Use Only

Audit No. Z223093

Received AUG 22 2016

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T517	Troy Saunders	20160720

0506E (2014/11) — Ministry's Copy — © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* **Tag#: A195956**

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT	K7S2H2	6132235184

Well Location

Address of Well Location (Stree: Number/Name)	Township	Lot	Concession
219 RIDGEMONT DR.	BECKWITH	14	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415418	5003883		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	LIMESTONE	GREY SANDSTONE		0	139

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³/ft³~~) yd³
0	50	BENTONITE GROUT	.576
50	60	CEMENT GROUT	.130

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Depth (m/ft) From	To	Hole Diameter (cm/in)
120 (m/ft) ☐ Gas ☐ Other, specify HYDRO FRAC	☐ Fresh ☒ Untested	60	139	6"
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEAR

If pumping discontinued, give reason:

Pump intake set at (m/ft): 129

Pumping rate (l/min / GPM): 6

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 40.59

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 129

Recommended pump rate (l/min / GPM): 6

Well production (l/min / GPM): 8

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	37.98		
1	39.67	1	38.40
2	39.95	2	37.85
3	40.27	3	37.75
4	40.41	4	
5	40.49	5	
10	40.53	10	
15	40.59	15	
20	40.59	20	
25	40.61	25	
30	40.61	30	
40	40.58	40	
50	40.59	50	
60	40.59	60	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR.	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. *(inc. area code)*	Name of Well Technician (Last Name, First Name)
6136235048	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T517	Troy Saunders	20161006

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2016 09 06	2016 09 06

Ministry Use Only

Audit No. Z223096

SEP 20 2016

Received

0506E (2014/11)

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* **A195942**

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT	K7S2H2	6132235184

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
213 RIDGEMONT DR	BECKWITH	15	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415386	5003913		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	LIMESTONE	BLACK LIMESTONE	RED+GREEN SHALE	0	83
GREY	LIMESTONE	GREY SANDSTONE	RED SANDSTONE	83	139

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³/ft³~~) yd³
0	50	BENTONITE GROUT	.480
50	60	CEMENT GROUT	.130

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Depth (m/ft) From	To	Hole Diameter (cm/in)
83 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	60	139	6"
83-139 (m/ft) ☐ Gas ☐ Other, specify HYDRO FRAC	☐ Fresh ☒ Untested			
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEAR/CLOUDY

If pumping discontinued, give reason:

Pump intake set at (m/ft): 130

Pumping rate (l/min / GPM): 5

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 46.98

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min / GPM): 6

Well production (l/min / GPM): 6

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	26.0		
1	32.98	1	38.40
2	36.30	2	34.12
3	38.01	3	31.55
4	39.02	4	29.43
5	39.76	5	28.10
10	42.42	10	26.0
15	44.0	15	
20	45.15	20	
25	45.60	25	
30	45.95	30	
40	46.34	40	
50	46.64	50	
60	46.98	60	

Map of Well Location

Please provde a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS TROY	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. *(inc. area code)*	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T517	Troy Saunders	20160723

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	20160623	20160623

Ministry Use Only

Audit No. Z223095

AUG 12 2016

Received

0506E (2014/11)

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A213224

Well Record

Regulation 903 Ontario Water Resources Act

Page _____ of _____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G ARGUE DR.	STITTSVILLE	ONT.	K7S2H2	6132235184

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
172 RIDGEMONT DR.	BECKWITH		

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415172	5004004		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY	STONES		0	7
GREY	LIMESTONE	BLACK LIMESTONE		7	140

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³ / yd³)
0	60	BENTONITE GROUT	0.640

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify _____

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify _____

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	0.188	0 ft	60

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify _____ ☐ Other, specify _____

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Hole Diameter Depth To	Diameter (cm/in)
117 ft	☐ Fresh ☒ Untested ☐ Gas ☐ Other, specify	60	140	6"
(m/ft)	☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify			
(m/ft)	☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason: _____

Pump intake set at (m/ft): 130

Pumping rate (l/min / GPM): 6

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 70.23

If flowing give rate (l/min / GPM): _____

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min / GPM): 5

Well production (l/min / GPM): 5

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	25.55		
1	29.30	1	66.63
2	32.87	2	63.22
3	35.69	3	59.98
4	38.25	4	56.58
5	40.20	5	53.38
10	47.80	10	43.60
15	55.05	15	33.96
20	60.02	20	29.62
25	63.05	25	27.17
30	65.43	30	25.88
40	67.00	40	25.58
50	68.73	50	25.55
60	70.23	60	25.55

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
1511 7	Troy Saul	2017/02/28

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/01/31	2017/01/31

Ministry Use Only

Audit No. Z243284

Received FEB 17 2017

0506E (2014/11)

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A195975

Well Record

Regulation 903 Ontario Water Resources Act

Page _____ of _____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G ARGUE DR.	STITTSVILLE	ONT.	K7S2H2	6132235184

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
163 RIDGEMONT DR	BECKWITH		

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415226	5004090		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	LIMESTONE	LAYERS OF WHITE SANDSTONE		0	240

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³ / yd³)
0	61	BENTONITE GROUT	0.896

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify _____

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify _____

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	0.188	0 ft	61

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify _____ ☐ Other, specify _____

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Hole Diameter Depth To	Diameter (cm/in)
127 ft	☐ Fresh ☒ Untested ☐ Gas ☐ Other, specify	61	240	6"
235 (m/ft)	☐ Fresh ☒ Untested ☐ Gas ☐ Other, specify			
(m/ft)	☐ Fresh ☐ Untested ☐ Gas ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was: ☒ Clear and sand free ☐ Other, specify _____

If pumping discontinued, give reason: _____

Pump intake set at (m/ft): 230

Pumping rate (l/min / GPM): 10

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 29.93

If flowing give rate (l/min / GPM): _____

Recommended pump depth (m/ft): 230

Recommended pump rate (l/min / GPM): 10

Well production (l/min / GPM): 1.5

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	28.78		
1	29.96	1	28.90
2	29.97	2	28.90
3	29.95	3	28.89
4	29.91	4	28.89
5	29.90	5	28.89
10	29.90	10	28.85
15	29.90	15	28.82
20	29.90	20	28.79
25	29.90	25	28.79
30	29.90	30	28.78
40	29.93	40	28.78
50	29.93	50	28.78
60	29.93	60	28.78

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6135229876	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
1511 7	Troy Saul	2017/01/05

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/01/05	2017/01/05

Ministry Use Only

Audit No. Z243269

Received JAN 20 2017

0506E (2014/11)

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A213245

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G. ARGUE DR.	STITTSVILLE	ONT.		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
197 RIDGEMONT DR.	BECKWITH	16	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415349	5003947		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	BLASTED ROCK		FILL	0	2
BROWN+YELLOW	CLAY			2	4
GREY	LIMESTONE			4	140

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³)
0	60	BENTONITE GROUT	.768

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify ____

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify ____

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ____ ☐ Other, specify ____

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	To	Diameter (cm/in)
129 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify HYDRO FRAC	60	140	6"
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 135

Pumping rate (l/min / GPM): 10

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 63.40

If flowing give rate (l/min / GPM)

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min / GPM): 8

Well production (l/min / GPM): 8

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		20.63		
1	1	26.40	1	56.35
2	2	29.69	2	51.20
3	3	31.62	3	46.70
4	4	33.36	4	42.50
5	5	35.16	5	38.82
10	10	41.72	10	26.15
15	15	46.28	15	21.35
20	20	49.83	20	20.70
25	25	52.60	25	20.64
30	30	54.63	30	20.63
40	40	58.12	40	20.63
50	50	61.69	50	20.63
60	60	63.40	60	20.63

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING	4819

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235048	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T5117	Troy Saunders	2017/06/12

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/05/12	2017/05/12

Ministry Use Only

Audit No. Z260668

Received JUN 15 2017

0506E (2014/11) Ministry's Copy © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☐ Imperial

Well Tag No. (Place Sticker and/or Print Below): A213226

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G. ARGUE DR	STITTSVILLE	ONT		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
234 RIDGEMONT DR.	BECKWITH	12	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415559	5003768		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	BROKEN ROCK		FILL	0	1
YELLOW	CLAY			1	5
BLACK	LIMESTONE			5	9½
GREY	LIMESTONE	LAYERS OF BLACK LIMESTONE + GREEN SHALE		9½	140

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³)
0	60	BENTONITE GROUT	.650

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify ____

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify ____

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ____ ☐ Other, specify ____

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	To	Diameter (cm/in)
70 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	60	140	6
120 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify HYDRO FRAC			
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 130

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 44.61

If flowing give rate (l/min / GPM)

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min / GPM): 8

Well production (l/min / GPM): 9

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		27.40		
1	1	53.30	1	38.12
2	2	35.04	2	32.92
3	3	36.50	3	29.51
4	4	38.03	4	28.32
5	5	38.91	5	28.13
10	10	41.79	10	27.93
15	15	42.84	15	27.68
20	20	43.49	20	27.57
25	25	43.88	25	27.57
30	30	43.98	30	27.55
40	40	44.21	40	27.54
50	50	44.35	50	27.54
60	60	44.61	60	27.53

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING	4819

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235048	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T5117	Troy Saunders	2017/06/16

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/05/16	2017/05/16

Ministry Use Only

Audit No. Z260669

Received JUN 15 2017

0506E (2014/11) Ministry's Copy © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* A227986

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G. ARGUE DR	STITTSVILLE	ONT		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
182 RIDGEMONT DR	BECKWITH	7	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	414522	5003968		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY	SHALE		0	4½
GREY	LIMESTONE	GREEN SHALE	LAYERS	4½	140

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³/ft³~~) yd³
0	60	BENTONITE GROUT	.768

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify ____

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify ____

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0 +2	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ____ ☐ Other, specify ____

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Other, specify
80 ~~ft~~ (m/ft) ☐ Gas	☐ Fresh ☐ Untested	☐ Other, specify HYDRO FRACK
Water found at Depth (m/ft) ☐ Gas	☐ Fresh ☐ Untested	☐ Other, specify ____
Water found at Depth (m/ft) ☐ Gas	☐ Fresh ☐ Untested	☐ Other, specify ____

Hole Diameter

Depth (m/ft) From	Depth (m/ft) To	Diameter (cm/in)
60	140	6

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4819

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR.	BRACESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136255048	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T517	Troy Saunders	2017/11/10

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason: ____

Pump intake set at (m/ft): 130

Pumping rate (l/min / GPM): 6

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 36.0

If flowing give rate (l/min / GPM): ____

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min / GPM): 7

Well production (l/min / GPM): 7

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		27.94		
1	1	31.43	1	32.40
2	2	32.40	2	30.0
3	3	32.95	3	28.70
4	4	33.25	4	28.0
5	5	33.50	5	28.0
10	10	34.40	10	27.95
15	15	34.83	15	27.94
20	20	35.02	20	27.94
25	25	35.20	25	27.94
30	30	35.32	30	27.94
40	40	35.85	40	27.94
50	50	35.92	50	27.94
60	60	36.0	60	27.94

Map of Well Location

Please provide a map below following instructions on the back.



Comments: ____

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/10/10	2017/10/60

Ministry Use Only

Audit No. Z260689

OCT 31 2017

Received

0506E (2014/11)

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* A213227

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G. ARGUE DR.	STITTSVILLE	ONT.		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
191 RIDGEMONT DR.	BECKWITH	17	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415328	5003971		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	SHALE	LOAM		0	5½
GREY	LIMESTONE	LAYERS OF RED & GREEN SHALE		5½	140

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³/ft³~~) yd³
0	60	BENTONITE GROUT	.650

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify ____

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify ____

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0 +2	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ____ ☐ Other, specify ____

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Other, specify
82½ (m/ft) ☐ Gas	☐ Fresh ☒ Untested	☐ Other, specify HYDRO FRAC
132½ (m/ft) ☐ Gas	☐ Fresh ☒ Untested	☐ Other, specify HYDRO FRAC
Water found at Depth (m/ft) ☐ Gas	☐ Fresh ☐ Untested	☐ Other, specify ____

Hole Diameter

Depth (m/ft) From	Depth (m/ft) To	Diameter (cm/in)
60	140	6"

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING	4819

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR.	BRACESIDE

Province	Postal Code	Business E-mail Address
ONT.	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T517	Troy Saunders	2017/06/13

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason: ____

Pump intake set at (m/ft): 130

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 27.77

If flowing give rate (l/min / GPM): ____

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min / GPM): 10

Well production (l/min / GPM): 12

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		23.44		
1	1	26.85	1	23.55
2	2	27.10	2	23.44
3	3	27.28	3	23.44
4	4	27.36	4	23.44
5	5	27.47	5	23.44
10	10	27.55	10	23.44
15	15	27.62	15	23.44
20	20	27.66	20	23.44
25	25	27.70	25	23.44
30	30	27.71	30	23.44
40	40	27.73	40	23.44
50	50	27.75	50	23.44
60	60	27.77	60	23.44

Map of Well Location

Please provide a map below following instructions on the back.



Comments: ____

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/05/13	2017/05/13

Ministry Use Only

Audit No. Z260670

JUN 15 2017

Received

0506E (2014/11)

Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A213255

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR	STITTSVILLE	ONT.		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
179 RIDGEMONT DR	BECKWITH	~~19~~ 18	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates Zone	Easting	Northing	Municipal Plan and Subiot Number	Other
NAD 83 18	441526	5004011		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY	LOAM, STONES	FILL	0	1
YELLOW	CLAY			1	6±
GREY	LIMESTONE	LAYERS OF GREEN & RED SHALE		6±	120

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³~~ yd³)
0	50	BENTONITE GROUT	.690
50	60	CEMENT GROUT	.130

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0±2	60

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Hole Diameter Depth To	Hole Diameter (cm/in)
63 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	60	120	6
92 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested			
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 110

Pumping rate (l/min / GPM): 12

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 32.30

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 110

Recommended pump rate (l/min / GPM): 12

Well production (l/min / GPM): 15+

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		26.53		
1	29.60	1	29.0	
2	30.45	2	28.90	
3	31.0	3	28.20	
4	31.32	4	28.0	
5	31.55	5	27.90	
10	32.0	10	27.60	
15	32.10	15	27.40	
20	32.20	20	27.25	
25	32.32	25	27.01	
30	32.20	30	26.86	
40	32.30	40	26.79	
50	32.30	50	26.75	
60	32.30	60	26.74	

Map of Well Location

Please provide a map below following instructons on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/09/28	2017/09/28

Ministry Use Only
Audit No. Z260690
OCT 31 2017
Received

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRACEBRIDGE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. *(inc. area code)*	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T5117	Troy Saunders	2017/10/28

0506E (2014/11) Ministry's Copy © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A227987

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR	STITTSVILLE	ONT.		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
222 RIDGEMONT	BECKWITH	11	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates Zone	Easting	Northing	Municipal Plan and Subiot Number	Other
NAD 83 18	441534	5003807		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY, LOAM, SHALE		FILL	0	3
SHALE	BROKEN LIMESTONE			3	5±
GREY	LIMESTONE	GREEN & RED SHALE LAYERS		5±	120

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³~~ yd³)
0	60	BENTONITE GROUT	.768

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0±2	60

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Hole Diameter Depth To	Hole Diameter (cm/in)
83 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	60	120	6
108 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested			
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 110

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 47.94

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 110

Recommended pump rate (l/min / GPM): 8

Well production (l/min / GPM): 10

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		36.20		
1	40.0	1	43.90	
2	41.80	2	39.40	
3	43.15	3	37.30	
4	44.20	4	36.45	
5	45.35	5	36.30	
10	46.70	10	36.25	
15	47.35	15	36.20	
20	47.55	20	36.20	
25	47.70	25	36.20	
30	47.75	30	36.20	
40	47.85	40	36.20	
50	47.90	50	36.20	
60	47.94	60	36.20	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2017/10/10	2017/10/10

Ministry Use Only
Audit No. Z260700
OCT 31 2017
Received

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRACEBRIDGE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. *(inc. area code)*	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T5117	Troy Saunders	2017/10/10

0506E (2014/11) Ministry's Copy © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A252424

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT.	K2S2H2	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
151 RIDGEMONT DR.	BECKWITH	21	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415721	5004114		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	SAND	STONES		0	1
GREY	LIMESTONE		FRACTURED	1	2
GREY	LIMESTONE	LAYERS OF GREY SANDSTONE		2	180

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³~~) yd³
0	60	BENTONITE GROUT	.896

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0 +5	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
83 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify			
120-180 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify HYDRO FRACK	60	180	6"
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 170

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 24.40

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 170

Recommended pump rate (l/min / GPM): 10

Well production (l/min / GPM): 10+

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		20.25		
1	25.0		1	20.25
2	24.5		2	20.25
3	24.30		3	20.25
4	24.25		4	20.25
5	24.25		5	20.25
10	24.30		10	20.25
15	24.30		15	20.25
20	24.35		20	20.25
25	24.35		25	20.25
30	24.35		30	20.25
40	24.40		40	20.25
50	24.40		50	20.25
60	24.40		60	20.25

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD — Well Contractor's Licence No.: 4817 9

Business Address (Street Number/Name): 1680 SCHEEL DR — Municipality: BRAESIDE

Province: ONT. — Postal Code: K0A1G0 — Business E-mail Address:

Bus. Telephone No. *(inc. area code)*: 6135623564 8 — Name of Well Technician (Last Name, First Name):

Well Technician's Licence No.: T5117 — Signature of Technician and/or Contractor — Date Submitted: 2018/10/10

Well owner's information package delivered	Date Package Delivered	Ministry Use Only
☒ Yes ☐ No	2018/12/10	Audit No. Z292769
	Date Work Completed: 2018/12/10	JAN 07 2019
		Received

0506E (2014/11) — Ministry's Copy — © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A228006

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT	K2S2H2	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
212 RIDGEMONT DR	BECKWITH	10	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415311	5001384 9		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	FILL			0	2
BROWN	LOAM	SHALE		2	4
GREY	LIMESTONE	BLACK LIMESTONE		4	180
		GREY SANDSTONE			
		+ GREEN SHALE LAYERS			

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³~~) yd³
0	60	BENTONITE GROUT	.910

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0 +2	60

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
128 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify			
171 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	60	180	6¼"
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 170

Pumping rate (l/min / GPM): 15

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 31.45

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 170

Recommended pump rate (l/min / GPM): 15

Well production (l/min / GPM): 15+

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		31.20		
1	31.25		1	31.20
2	31.40		2	31.20
3	31.43		3	31.20
4	31.43		4	31.20
5	31.43		5	31.20
10	31.45		10	31.20
15	31.45		15	31.20
20	31.45		20	31.20
25	31.45		25	31.20
30	31.45		30	31.20
40	31.45		40	31.20
50	31.45		50	31.20
60	31.45		60	31.20

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD — Well Contractor's Licence No.: 4817 9

Business Address (Street Number/Name): 1680 SCHEEL DR — Municipality: BRAESIDE

Province: ONT — Postal Code: K0A1G0 — Business E-mail Address:

Bus. Telephone No. *(inc. area code)*: 6135623564 8 — Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: T5117 — Signature of Technician and/or Contractor — Date Submitted: 2018/04/07

Well owner's information package delivered	Date Package Delivered	Ministry Use Only
☒ Yes ☐ No	2018/03/07	Audit No. Z260717
	Date Work Completed: 2018/03/07	MAR 27 2018
		Received

0506E (2014/11) — Ministry's Copy — © Queen's Printer for Ontario, 2014

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A252405

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT.	K2S2H2	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
241 RIDGEMONT DR.	BECKWITH	18	PHASE 2

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415461	5003808		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	LIMESTONE	LAYERS OF BLACK LIMESTONE		0	200

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³) yd³
0	60	BENTONITE GROUT	.768

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0+	60

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Depth (m/ft) From	To	Hole Diameter (cm/in)
78 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	60	200	6¼
184 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify			
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 190

Pumping rate (l/min / GPM): 7

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 30.90

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 190

Recommended pump rate (l/min / GPM): 8

Well production (l/min / GPM):

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	28.15			
1	30.10	1	28.40	
2	30.25	2	28.25	
3	30.40	3	28.25	
4	30.75	4	28.23	
5	30.75	5	28.23	
10	30.75	10	28.20	
15	30.80	15	28.20	
20	30.80	20	28.18	
25	30.85	25	28.15	
30	30.85	30	28.15	
40	30.90	40	28.15	
50	30.90	50	28.15	
60	30.90	60	28.15	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD — Well Contractor's Licence No.: 4819

Business Address (Street Number/Name): 1680 SCHEEL DR — Municipality: BRAESIDE

Province: ONT — Postal Code: K0A1G0 — Business E-mail Address:

Bus. Telephone No. *(inc. area code)*: 6136235648 — Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: 1517 — Signature of Technician and/or Contractor — Date Submitted: 2019 05 15

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2019 05 15	2019 05 15

Ministry Use Only

Audit No. Z292766

Received MAY 07 2019

0506E (2014/11) Ministry's Copy

Ontario — Ministry of the Environment and Climate Change

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A252425

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT	K2S2H2	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
190 RIDGEMONT	BECKWITH	8	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415258	5003926		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY	LOAM		0	1½
GREY	LIMESTONE	LAYERS OF GREEN SHALE		1½	120

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³) yd³
0	60	BENTONITE GROUT	.896

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	To
6¼	STEEL	.188	0+	60

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	To

Water Details

Water found at Depth	Kind of Water	Depth (m/ft) From	To	Hole Diameter (cm/in)
84 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify			
105 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	60	120	6¼
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 110

Pumping rate (l/min / GPM): 12

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 24.65

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 110

Recommended pump rate (l/min / GPM): 12

Well production (l/min / GPM): 12+

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	19.80			
1	22.80	1	20.70	
2	23.45	2	20.50	
3	23.65	3	20.50	
4	23.90	4	20.45	
5	24.0	5	20.40	
10	24.30	10	20.22	
15	24.40	15	20.05	
20	24.45	20	19.88	
25	24.50	25	19.85	
30	24.55	30	19.84	
40	24.60	40	19.84	
50	24.65	50	19.82	
60	24.65	60	19.82	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD — Well Contractor's Licence No.: 4819

Business Address (Street Number/Name): 1680 SCHEEL DR. — Municipality: BRAESIDE

Province: ONT — Postal Code: K0A1G0 — Business E-mail Address:

Bus. Telephone No. *(inc. area code)*: 6136235648 — Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: 1517 — Signature of Technician and/or Contractor — Date Submitted: 2019 04 09

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2018 12 08	2018 12 08

Ministry Use Only

Audit No. Z292768

Received JAN 07 2019

0506E (2014/11) Ministry's Copy

Ontario — Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A276752

Well Record

Regulation 903 Ontario Water Resources Act

Page _____ of _____

[redacted]

Well Location

Address of Well Location (Street Number/Name): 254 RIDGEMONT DR.
Township: BECKWITH
Lot:
Concession:
County/District/Municipality: LANARK
City/Town/Village: ASHTON
Province: Ontario
Postal Code:
UTM Coordinates: NAD 83 Zone 18 Easting 415423 Northing 5003689
Municipal Plan and Sublot Number:
Other:

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	LOAM	SHALE, CLAY		0	4½
GREY	LIMESTONE	LAYERS OF RED & GREEN SHALE		4½	99

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/~~ft³~~) yd³
0	60	BENTONITE GROUT	0.768

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0+2	60
6	OPEN HOLE		60	99

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth (m/ft)	Gas	Other, specify	Kind of Water: Fresh	Untested
84	☐	☐	☐	☒

Hole Diameter

Depth (m/ft) From	Depth (m/ft) To	Diameter (cm/in)
0	60	9¾
60	99	6

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 89

Pumping rate (l/min / GPM): 12

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 36.10

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 89

Recommended pump rate (l/min / GPM): 12

Well production (l/min / GPM):

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	34.25		
1	35.10	1	34.50
2	36.0	2	34.30
3	36.02	3	34.25
4	36.0	4	34.25
5	36.05	5	34.25
10	36.02	10	34.25
15	36.05	15	34.25
20	36.05	20	34.25
25	36.10	25	34.25
30	36.10	30	34.25
40	36.10	40	34.25
50	36.10	50	34.25
60	36.10	60	34.25

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD
Well Contractor's Licence No.: 4879
Business Address (Street Number/Name): 1680 SCHEEL DR
Municipality: BRAESIDE
Province: ONT
Postal Code: K0A 1G0
Business E-mail Address:
Bus. Telephone No. (inc. area code): 6136235648
Name of Well Technician (Last Name, First Name): SAUNDERS TROY
Well Technician's Licence No.: T517
Signature of Technician and/or Contractor:
Date Submitted: 2019/12/30

Well owner's information package delivered: ☒ Yes ☐ No
Date Package Delivered: 2019/12/16
Date Work Completed: 2019/12/19

Ministry Use Only

Audit No. Z318991
JAN 27 2020
Received

0506E (2018/12) Ministry's Copy © Queen's Printer for Ontario, 2018

Ontario — Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)*: A276761

Well Record

Regulation 903 Ontario Water Resources Act

Page _____ of _____

Well Owner's Information

First Name:
Last Name / Organization: TOMAR CUSTOM HOMES
E-mail Address:
☐ Well Constructed by Well Owner
Mailing Address (Street Number/Name): 54 BERT G. ARGUE DR
Municipality: STITTSVILLE
Province: ONT
Postal Code: K7S2H2
Telephone No. *(inc. area code)*:

Well Location

Address of Well Location (Street Number/Name): 325 RIDGEMONT DR.
Township: BECKWITH
Lot: 10
Concession:
County/District/Municipality: LANARK
City/Town/Village: ASHTON PHASE 2
Province: Ontario
Postal Code:
UTM Coordinates: NAD 83 Zone 18 Easting 415700 Northing 5003454
Municipal Plan and Sublot Number:
Other:

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	CLAY	SANDY STONES	FILL	0	4
BROWN	HUMUS			4	6
BROWN	CLAY			6	8
GREY	LIMESTONE	LAYERS OF GREY SANDSTONE		8	124
		LAYERS OF GREEN & RED SHALE			

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/~~ft³~~) yd³
0	60	BENTONITE GROUT	0.765

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0+2	60
6	OPEN HOLE		60	124

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth (m/ft)	Gas	Other, specify	Kind of Water: Fresh	Untested
87	☐	☐	☐	☒
114	☐	☐	☐	☒

Hole Diameter

Depth (m/ft) From	Depth (m/ft) To	Diameter (cm/in)
0	60	9¾
60	124	6

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 114

Pumping rate (l/min / GPM): 10

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 42.10

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 114

Recommended pump rate (l/min / GPM): 10

Well production (l/min / GPM): 10+

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	34.30		
1	39.02	1	35.16
2	39.23	2	34.35
3	40.08	3	34.31
4	40.58	4	34.30
5	40.85	5	34.30
10	41.43	10	34.30
15	41.62	15	34.30
20	41.63	20	34.30
25	41.78	25	34.30
30	41.80	30	34.30
40	41.92	40	34.30
50	42.0	50	34.30
60	42.10	60	34.30

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD
Well Contractor's Licence No.: 4879
Business Address (Street Number/Name): 1680 SCHEEL DR
Municipality: BRAESIDE
Province: ONT
Postal Code: K0A 1G0
Business E-mail Address:
Bus. Telephone No. (inc. area code): 6136235648
Name of Well Technician (Last Name, First Name): SAUNDERS TROY
Well Technician's Licence No.: T517
Signature of Technician and/or Contractor:
Date Submitted: 2019/12/20

Well owner's information package delivered: ☒ Yes ☐ No
Date Package Delivered: 2019/12/04
Date Work Completed: 2019/12/04

Ministry Use Only

Audit No. Z318977
Received DEC 20 2019

0506E (2018/12) Ministry's Copy © Queen's Printer for Ontario, 2018

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* A276753

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT.	K7S2H2	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
310 RIDGEMONT DR	BECKWITH	8 PHASE 2	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK		Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415590	5003470		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	SHALE		FILL	0	1½
YELLOW	CLAY			1½	4
GREY	LIMESTONE			4	160

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
0	60	BENTONITE GROUT	.896 yd³

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0	60
6	OPEN HOLE		60	160

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth (m/ft)	Gas	Kind of Water: Fresh	Untested	Other, specify
68	☐	☐	☒	
109	☐	☐	☒	
148	☐	☐	☒	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	60	9¾
60	160	6

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 150

Pumping rate (l/min / GPM): 6.5

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 51.46

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 150

Recommended pump rate (l/min / GPM): 7

Well production (l/min / GPM):

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	29.05		
1	32.50	1	47.35
2	35.04	2	43.75
3	38.30	3	40.63
4	39.27	4	37.90
5	40.16	5	35.55
10	43.47	10	29.54
15	45.70	15	29.05
20	47.90	20	29.05
25	48.40	25	29.05
30	49.03	30	29.05
40	50.15	40	29.05
50	50.90	50	29.05
60	51.46	60	29.05

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD. — Well Contractor's Licence No.: 4879

Business Address (Street Number/Name): 1680 SCHEEL DR — Municipality: BRAESIDE

Province: ONT — Postal Code: K0A1G0 — Business E-mail Address:

Bus. Telephone No. *(inc. area code)*: 6135623648 — Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: T517 — Signature of Technician and/or Contractor: Troy Saunders — Date Submitted: 2019/12/20

Well owner's information package delivered: ☒ Yes ☐ No — Date Package Delivered: 2019/12/16

Date Work Completed: 2019/12/16

Ministry Use Only

Audit No. Z318978

Received JAN 28 2020

0506E (2018/12) Ministry's Copy

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* A276739

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
54 BERT G. ARGUE DR.	STITTSVILLE	ONT	K7S2H2	

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
255 RIDGEMONT DR	BECKWITH	17 PHASE 2	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415503	5003751		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	BROKEN ROCK		FILL	0	1
BROWN	CLAY	STONES		1	3
GREY	LIMESTONE	LAYERS OF GREY	SANDSTONE	3	180

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
0	60	BENTONITE GROUT	.896 yd³

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0	60
6	OPEN HOLE		60	180

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth (m/ft)	Gas	Kind of Water: Fresh	Untested	Other specify
80	☐	☐	☒	HYDRO FRACK
	☐	☐	☐	
	☐	☐	☐	

Hole Diameter

Depth (m/ft) From	To	Diameter (cm/in)
0	60	9¾
60	180	6

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 170

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 70.75

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 170

Recommended pump rate (l/min / GPM): 8

Well production (l/min / GPM):

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	44.90		
1	49.0	1	68.50
2	50.70	2	60.40
3	51.85	3	55.75
4	53.70	4	53.30
5	54.85	5	51.10
10	60.35	10	45.30
15	63.75	15	45.05
20	66.0	20	44.95
25	67.60	25	44.90
30	68.40	30	44.90
40	69.75	40	44.90
50	70.30	50	44.90
60	70.75	60	44.90

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD. — Well Contractor's Licence No.: 4879

Business Address (Street Number/Name): 1680 SCHEEL DR — Municipality: BRAESIDE

Province: ONT — Postal Code: K0A1G0 — Business E-mail Address:

Bus. Telephone No. *(inc. area code)*: 6135623648 — Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: T517 — Signature of Technician and/or Contractor: Troy Saunders — Date Submitted: 2019/12/20

Well owner's information package delivered: ☒ Yes ☐ No — Date Package Delivered: 2019/12/18

Date Work Completed: 2019/11/16

Ministry Use Only

Audit No. Z318976

Received JAN 27 2020

0506E (2018/12) Ministry's Copy

Draw Down & Recovery

Draw Down Time(min)	Draw Down Water level	Recovery Time(min)	Recovery Water level
SWL	30.35 ft		
1	31 ft	1	30.5 ft
2	31 ft	2	30.46 ft
3	31.05 ft	3	30.43 ft
4	31.09 ft	4	30.42 ft
5	31.05 ft	5	30.41 ft
10	31.08 ft	10	30.4 ft
15	31.1 ft	15	30.38 ft
20	31.1 ft	20	30.37 ft
25	31.1 ft	25	30.37 ft
30	31.12 ft	30	30.36 ft
40	31.12 ft	40	30.35 ft
45		45	
50	31.13 ft	50	30.35 ft
60	31.15 ft	60	30.35 ft

Water Details

Water Found at Depth	Kind
79 ft	Untested
93 ft	Untested

Hole Diameter

Depth From	Depth To	Diameter
0 ft	60.5 ft	9.75 Inch
60.5 ft	120 ft	6.125 Inch

Audit Number: 2334321

Date Well Completed: March 12, 2020

Date Well Record Received by MOE: March 31, 2020

Well ID

Well ID Number: 7356155
Well Audit Number: 2334321
Well Tag Number: 4276774
This table contains information from the original well record and any subsequent updates.

Well Location

Address of Well Location	277 Ridgemont Dr
Township	BECKWITH TOWNSHIP
Lot	
Concession	
County/District/Municipality	LANARK
City/Town/Village	ASHTON
Province	ON
Postal Code	n/a
UTM Coordinates	NAD83 — Zone 18 Easting: 415585.00 Northing: 5003664.00
Municipal Plan and Sublot Number	
Other	

Overburden and Bedrock Materials Interval

General Colour	Most Common Material	Other Materials	General Description	Depth From	Depth To
GREY	LMSN	SNDS	SHLE	0 ft	120 ft

Annular Space/Abandonment Sealing Record

Depth From	Depth To	Type of Sealant Used (Material and Type)	Volume Placed
0 ft	60.5 ft	BENTONITE GROUT	

Method of Construction & Well Use

Method of Construction	Well Use
Air Percussion	
	Domestic

Status of Well

Water Supply

Construction Record - Casing

Inside Diameter	Open Hole or material	Depth From	Depth To
6.25 Inch	STEEL	-.583 ft	60.5 ft
6.125 Inch	OPEN HOLE	60.5 ft	120 ft

Construction Record - Screen

Outside Diameter	Material	Depth From	Depth To

Well Contractor and Well Technician Information

Well Contractor's Licence Number: 4879

Well Contractor and Well Technician Information

Well Contractor's Licence Number: 4879

Results of Well Yield Testing

After test of well yield, water was	OTHER
If pumping discontinued, give reason	
Pump intake set at	110 ft
Pumping Rate	14 GPM
Duration of Pumping	1 h:0 m
Final water level	31.15 ft
If flowing give rate	
Recommended pump depth	10 ft
Recommended pump rate	14 GPM
Well Production	
Disinfected?	Y

Ontario — Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* A296814

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
BERT G ARGUE DR	STITTSVILLE	ONT		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
295 RIDGEMONT DR.	BECKWITH	12	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415645	5003570		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	ROCK		FILL	0	2½
BROWN	CLAY	SHALE		2½	4
GREY	LIMESTONE	GREY SANDSTONE		4	160

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³~~) yd³
0	60	BENTONITE GROUT	.768

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
5¼	STEEL	.188	0 +2	60
5⅛	OPEN HOLE		60	160

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Depth To	Diameter (cm/in)
77 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	0	60	9¾
8 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested	60	160	6⅝
30 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested			

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 150

Pumping rate (l/min / GPM): 6

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 45.30

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 150

Recommended pump rate (l/min / GPM): 8

Well production (l/min / GPM): 8

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		39.3		
1	42.45	1	42.0	
2	43.35	2	40.40	
3	43.90	3	39.80	
4	44.32	4	39.70	
5	44.90	5	39.67	
10	45.45	10	39.55	
15	45.75	15	39.39	
20	45.55	20	39.37	
25	45.30	25	39.35	
30	45.25	30	39.31	
40	45.30	40	39.3	
50	45.30	50	39.3	
60	45.30	60	39.3	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR.	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. *(inc. area code)*	Name of Well Technician (Last Name, First Name)
1136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
7517	Troy Saul	2020 08 02

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2020 07 02	2020 07 02

Ministry Use Only
Audit No. Z334339
Received JUL 30 2020

506E (2018/12) **Ministry's Copy** © Queen's Printer for Ontario, 2018

Ontario — Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. *(Place Sticker and/or Print Below)* A296816

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name / Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. *(inc. area code)*
BERT G ARGUE DR	STITTSVILLE	ONT		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
259 RIDGEMONT DR	BECKWITH	16	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415536	5003747		

Overburden and Bedrock Materials/Abandonment Sealing Record *(see instructions on the back of this form)*

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
GREY	GRAVEL		FILL	0	1
BROWN	LOAM	CLAY + SHALE		1	3
GREY	LIMESTONE	LAYERS OF GREY SANDSTONE		3	91
GREY	SANDSTONE	LAYERS OF RED + GREEN SHALE		91	160

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (~~m³~~) yd³
0	60	BENTONITE GROUT	.640

Method of Construction

☐ Cable Tool ☐ Diamond
☐ Rotary (Conventional) ☐ Jetting
☐ Rotary (Reverse) ☐ Driving
☐ Boring ☐ Digging
☒ Air percussion
☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used
☒ Domestic ☐ Municipal ☐ Dewatering
☐ Livestock ☐ Test Hole ☐ Monitoring
☐ Irrigation ☐ Cooling & Air Conditioning
☐ Industrial
☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
5¼	STEEL	.188	0 +7	60
5⅛	OPEN HOLE		60	160

Status of Well

☒ Water Supply
☐ Replacement Well
☐ Test Hole
☐ Recharge Well
☐ Dewatering Well
☐ Observation and/or Monitoring Hole
☐ Alteration (Construction)
☐ Abandoned, Insufficient Supply
☐ Abandoned, Poor Water Quality
☐ Abandoned, other, specify
☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Depth To	Diameter (cm/in)
102 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	0	60	9¾
53 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	60	160	6⅝
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was:
☐ Clear and sand free
☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 150

Pumping rate (l/min / GPM): 14

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 62.80

If flowing give rate (l/min / GPM):

Recommended pump depth (m/ft): 150

Recommended pump rate (l/min / GPM): 12

Well production (l/min / GPM): 15

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		36.2		
1	42.80	1	53.10	
2	45.70	2	47.10	
3	48.50	3	43.55	
4	50.65	4	39.80	
5	52.40	5	37.80	
10	58.0	10	36.23	
15	59.60	15	36.20	
20	60.70	20	36.20	
25	61.35	25	36.20	
30	61.65	30	36.20	
40	62.30	40	36.20	
50	62.55	50	36.20	
60	62.80	60	36.20	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR.	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT.	K0A1G0	

Bus. Telephone No. *(inc. area code)*	Name of Well Technician (Last Name, First Name)
1136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
7517	Troy Saul	2020 08 01

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2020 07 01	2020 07 01

Ministry Use Only
Audit No. Z334345
Received JUL 30 2020

506E (2018/12) **Ministry's Copy** © Queen's Printer for Ontario, 2018

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A309683

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G ARGUE DR	STITTSVILLE	ONT.		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
244 RIDGEMONT DR	BECKWITH		

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415389	5003754		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	LOAM	SHALE		0	4
GREY	LIMESTONE	LAYERS OF GREEN SHALE & GREY SANDSTONE		4	140

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
0	60	BENTONITE GROUT	.640 yd³

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6 1/4	STEEL	.188	0 +2	60
6 1/16	OPEN HOLE		60	140

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
77 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	0	60	9 3/4
84 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	60	140	6 1/16
120 (m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
1680 SCHEEL	BRAESIDE	ONT.	K0A 1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)	Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
6136235648	SAUNDERS TROY	T517	Troy Saunders	2021 04 30

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 130

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 48.35

If flowing give rate (l/min/GPM):

Recommended pump depth (m/ft): 130

Recommended pump rate (l/min/GPM): 8

Well production (l/min/GPM): 9

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	29.35			
1	35.0	1	44.40	
2	37.50	2	40.0	
3	38.80	3	36.75	
4	39.70	4	34.20	
5	40.50	5	31.90	
10	43.0	10	30.50	
15	45.10	15	29.40	
20	46.35	20	29.35	
25	46.90	25	29.35	
30	47.10	30	29.35	
40	47.75	40	29.35	
50	48.10	50	29.35	
60	48.35	60	29.35	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2021 03 31	2021 03 31

Ministry Use Only

Audit No. Z349898

APR 12 2021

Received

0506E (2020/06) © Queen's Printer for Ontario, 2020

Ministry's Copy

Ontario — Ministry of the Environment, Conservation and Parks

Well Record

Regulation 903 Ontario Water Resources Act

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A296837

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT G ARGUE DR.	STITTSVILLE	ONT		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
309 RIDGEMONT DR.	BECKWITH	11 PHT-SE 2	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 8 3	18	415665	5003531		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	SAND	CLAY		0	6
GREY	SHALE			6	9
GREY	LIMESTONE			9	180

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
0	60	BENTONITE GROUT	.704 yd³

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6 1/4	STEEL	.188	0 +5	60
6 1/16	OPEN HOLE		60	180

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth (m/ft) From	To	Diameter (cm/in)
89 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	0	60	9 3/4
160 (m/ft) ☐ Gas	☐ Fresh ☒ Untested ☐ Other, specify	60	180	6 1/16
(m/ft) ☐ Gas	☐ Fresh ☐ Untested ☐ Other, specify			

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality	Province	Postal Code	Business E-mail Address
1680 SCHEEL DR	BRAESIDE	ONT	K0A 1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)	Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
6136235648	SAUNDERS TROY	T517	Troy Saunders	2020 10 30

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 170

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 57.25

If flowing give rate (l/min/GPM):

Recommended pump depth (m/ft): 170

Recommended pump rate (l/min/GPM): 8

Well production (l/min/GPM): 9

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	35.40			
1	42.70	1	52.10	
2	45.70	2	48.10	
3	47.60	3	43.30	
4	48.40	4	40.60	
5	49.60	5	38.15	
10	53.0	10	35.80	
15	55.0	15	35.65	
20	55.90	20	35.58	
25	56.40	25	35.52	
30	56.65	30	35.48	
40	56.90	40	35.45	
50	57.0	50	35.45	
60	57.25	60	35.44	

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Date Work Completed
☒ Yes ☐ No	2020 09 30	2020 09 30

Ministry Use Only

Audit No. Z349864

OCT 27 2020

Received

0506E (2020/06) © Queen's Printer for Ontario, 2020

Ministry's Copy

Ontario Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below) A309682

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

[redacted]

Address of Well Location (Street Number/Name): 288 RIDGEMONT DR. | Township: BECKWITH | Lot: 6 | Concession:

County/District/Municipality: LANARK | City/Town/Village: ASHTON | Province: Ontario | Postal Code:

UTM Coordinates: NAD 8 3 | Zone: 18 | Easting: 414155 | Northing: 4500355 3 | Municipal Plan and Sublot Number: | Other:

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	LOAM	CLAY & SHALE		0	5
GREY	LIMESTONE			5	85
GREY	LIMESTONE	LAYERS OF RED SANDSTONE		85	100

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³) yd³
0	60	BENTONITE GROUT	.640

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0 +2	60
6 1/16	OPEN HOLE		60	100

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Depth To	Diameter (cm/in)
67 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	0	60	9¾
92 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	60	100	6 1/16
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 75

Pumping rate (l/min / GPM): 12

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 24.85

If flowing give rate (l/min/GPM):

Recommended pump depth (m/ft): 75

Recommended pump rate (l/min/GPM): 12

Well production (l/min/GPM): 20+

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	24.0		
1	24.7	1	24.0
2	24.7	2	24.0
3	24.72	3	24.0
4	24.70	4	24.0
5	24.70	5	24.0
10	24.75	10	24.0
15	24.75	15	24.0
20	24.75	20	24.0
25	24.80	25	24.0
30	24.80	30	24.0
40	24.83	40	24.0
50	24.85	50	24.0
60	24.85	60	24.0

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD | Well Contractor's Licence No.: 4879

Business Address (Street Number/Name): 1680 SCHEEL DR. | Municipality: BRAESIDE

Province: ONT. | Postal Code: K0A1G0 | Business E-mail Address:

Bus. Telephone No. (inc. area code): 6136235648 | Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: T517 | Signature of Technician and/or Contractor | Date Submitted: 2021/04/30

Well owner's information package delivered: ☒ Yes ☐ No | Date Package Delivered: 2021/03/31 | Date Work Completed: 2021/03/31

Ministry Use Only: Audit No. Z349899 APR 12 2021 Received

0506E (2020/06) © Queen's Printer for Ontario, 2020 **Ministry's Copy**

Ontario Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below) A309684

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name | Last Name/Organization: TOMAR CUSTOM HOMES | E-mail Address | ☐ Well Constructed by Well Owner

Mailing Address (Street Number/Name): 54 BERT G. ARGUE DR. | Municipality: STITTSVILLE | Province: ONT. | Postal Code | Telephone No. (inc. area code)

Well Location

Address of Well Location (Street Number/Name): 270 RIDGEMONT DR. | Township: BECKWITH | Lot | Concession

County/District/Municipality: LANARK | City/Town/Village: ASHTON | Province: Ontario | Postal Code

UTM Coordinates: NAD 8 3 | Zone: 18 | Easting: 414155 | Northing: 4500361 0 | Municipal Plan and Sublot Number | Other

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	LOAM	CLAY & SHALE		0	9½
GREY	LIMESTONE	LAYERS OF BLACK LIMESTONE		9½	92
GREY	LIMESTONE	LAYERS OF GREY & RED SANDSTONE		92	176

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³) yd³
0	60	BENTONITE GROUT	.640

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0 +4	60

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Water Details

Water found at Depth	Kind of Water	Hole Diameter Depth From	Depth To	Diameter (cm/in)
166 (m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☒ Untested	0	60	9¾
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested	60	176	6 1/16
(m/ft) ☐ Gas ☐ Other, specify	☐ Fresh ☐ Untested			

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 160

Pumping rate (l/min / GPM): 8

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 53.0

If flowing give rate (l/min/GPM):

Recommended pump depth (m/ft): 160

Recommended pump rate (l/min/GPM): 8

Well production (l/min/GPM): 8

Disinfected? ☒ Yes ☐ No

Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level	30.10		
1	34.10	1	45.0
2	36.20	2	40.40
3	37.90	3	37.70
4	39.30	4	35.20
5	40.40	5	30.10
10	45.50	10	30.10
15	47.10	15	30.10
20	48.90	20	30.10
25	50.0	25	30.10
30	50.90	30	30.10
40	51.90	40	30.10
50	52.55	50	30.10
60	53.0	60	30.10

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well Contractor and Well Technician Information

Business Name of Well Contractor: SAUNDERS WELL DRILLING LTD | Well Contractor's Licence No.: 4879

Business Address (Street Number/Name): 1680 SCHEEL DR | Municipality: BRAESIDE

Province: ONT. | Postal Code: K0A1G0 | Business E-mail Address:

Bus. Telephone No. (inc. area code): 6136235648 | Name of Well Technician (Last Name, First Name): SAUNDERS TROY

Well Technician's Licence No.: T517 | Signature of Technician and/or Contractor | Date Submitted: 2021/04/30

Well owner's information package delivered: ☒ Yes ☐ No | Date Package Delivered: 2021/03/31 | Date Work Completed: 2021/03/31

Ministry Use Only: Audit No. Z349906 APR 12 2021 Received

0506E (2020/06) © Queen's Printer for Ontario, 2020 **Ministry's Copy**

Ontario — Ministry of the Environment, Conservation and Parks

Measurements recorded in: ☐ Metric ☒ Imperial

Well Tag No. (Place Sticker and/or Print Below): A309702

Well Record

Regulation 903 Ontario Water Resources Act

Page ____ of ____

Well Owner's Information

First Name	Last Name/Organization	E-mail Address	☐ Well Constructed by Well Owner
	TOMAR CUSTOM HOMES		

Mailing Address (Street Number/Name)	Municipality	Province	Postal Code	Telephone No. (inc. area code)
54 BERT GARGUE	STITTSVILLE	ONT		

Well Location

Address of Well Location (Street Number/Name)	Township	Lot	Concession
145 RIDGEMONT DR.	BECKWITH	22	

County/District/Municipality	City/Town/Village	Province	Postal Code
LANARK	ASHTON	Ontario	

UTM Coordinates	Zone	Easting	Northing	Municipal Plan and Sublot Number	Other
NAD 83	18	415163	5004149		

Overburden and Bedrock Materials/Abandonment Sealing Record (see instructions on the back of this form)

General Colour	Most Common Material	Other Materials	General Description	Depth (m/ft) From	Depth (m/ft) To
BROWN	LOAM			0	6"
GREY	SHALE			6"	1½
GREY	LIMESTONE	LAYERS OF GREEN SHALE		1½	120

Annular Space

Depth Set at (m/ft) From	To	Type of Sealant Used (Material and Type)	Volume Placed (m³/ft³)
0	60½	BENTONITE GROUT	[redacted]
			.650

Method of Construction

☐ Cable Tool ☐ Diamond ☐ Rotary (Conventional) ☐ Jetting ☐ Rotary (Reverse) ☐ Driving ☐ Boring ☐ Digging ☒ Air percussion ☐ Other, specify

Well Use

☐ Public ☐ Commercial ☐ Not used ☒ Domestic ☐ Municipal ☐ Dewatering ☐ Livestock ☐ Test Hole ☐ Monitoring ☐ Irrigation ☐ Cooling & Air Conditioning ☐ Industrial ☐ Other, specify

Construction Record - Casing

Inside Diameter (cm/in)	Open Hole OR Material (Galvanized, Fibreglass, Concrete, Plastic, Steel)	Wall Thickness (cm/in)	Depth (m/ft) From	Depth (m/ft) To
6¼	STEEL	.188	0+6	60½
6	OPEN HOLE		60½	120

Construction Record - Screen

Outside Diameter (cm/in)	Material (Plastic, Galvanized, Steel)	Slot No.	Depth (m/ft) From	Depth (m/ft) To

Status of Well

☒ Water Supply ☐ Replacement Well ☐ Test Hole ☐ Recharge Well ☐ Dewatering Well ☐ Observation and/or Monitoring Hole ☐ Alteration (Construction) ☐ Abandoned, Insufficient Supply ☐ Abandoned, Poor Water Quality ☐ Abandoned, other, specify ☐ Other, specify

Water Details

Water found at Depth (m/ft)	Gas	Kind of Water	Other, specify
61	☐	☐ Fresh ☒ Untested	
98+10	☐	☐ Fresh ☒ Untested	
	☐	☐ Fresh ☐ Untested	

Hole Diameter

Depth (m/ft) From	Depth (m/ft) To	Diameter (cm/in)
0	60½	9¾
60½	120	6

Well Contractor and Well Technician Information

Business Name of Well Contractor	Well Contractor's Licence No.
SAUNDERS WELL DRILLING LTD	4879

Business Address (Street Number/Name)	Municipality
1680 SCHEEL DR	BRAESIDE

Province	Postal Code	Business E-mail Address
ONT	K0A1G0	

Bus. Telephone No. (inc. area code)	Name of Well Technician (Last Name, First Name)
6136235648	SAUNDERS TROY

Well Technician's Licence No.	Signature of Technician and/or Contractor	Date Submitted
T5117	Troy Saunders	2021/06/05

Results of Well Yield Testing

After test of well yield, water was: ☐ Clear and sand free ☐ Other, specify CLEARING

If pumping discontinued, give reason:

Pump intake set at (m/ft): 110

Pumping rate (l/min / GPM): 10

Duration of pumping: 1 hrs + 0 min

Final water level end of pumping (m/ft): 27.50

If flowing give rate (l/min/GPM)

Recommended pump depth (m/ft): 110

Recommended pump rate (l/min/GPM): 10

Well production (l/min/GPM): 12

Disinfected? ☒ Yes ☐ No

	Draw Down Time (min)	Draw Down Water Level (m/ft)	Recovery Time (min)	Recovery Water Level (m/ft)
Static Level		23.90		
1	27.50		1	[redacted]29.25
2	27.30		2	23.90
3	27.25		3	23.90
4	27.30		4	23.90
5	27.30		5	23.90
10	27.35		10	23.90
15	27.37		15	23.90
20	27.40		20	23.90
25	27.40		25	23.90
30	27.40		30	23.90
40	27.45		40	23.90
50	27.45		50	23.90
60	27.50		60	23.90

Map of Well Location

Please provide a map below following instructions on the back.



Comments:

Well owner's information package delivered	Date Package Delivered	Ministry Use Only
☒ Yes ☐ No	2021/06/05	Audit No. Z361794
	Date Work Completed: 2021/06/05	Received: JUN 22 2021

0506E (2020/06) © Queen's Printer for Ontario, 2020

Ministry's Copy

APPENDIX IV

Laboratory Certificates

CADUCEON ENVIRONMENTAL LABORATORIES
Client committed. Quality assured. Canadian owned.

CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: G 130347

REPORT No: 24-032854 - Rev. 0

Report To:
Pinchin Ltd. - Kingston
1456 Centennial Dr, Suite 2
Kingston, ON K7P 0K4

CADUCEON Environmental Laboratories
285 Dalton Ave
Kingston, ON K7K 6Z1

Attention: Phil Tibble

DATE RECEIVED: 2024-Oct-21
DATE REPORTED: 2024-Oct-25
SAMPLE MATRIX: Ground Water

CUSTOMER PROJECT: 283258001
P.O. NUMBER:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	1	OTTAWA	PCURIEL	2024-Oct-23	A-IC-01	SM 4110B
Colour (Liquid)	1	OTTAWA	STAILLON	2024-Oct-23	A-COL-01	SM 2120C
Cond/pH/Alk Auto (Liquid)	1	OTTAWA	SBOUDREAU	2024-Oct-23	COND-02/PH-02/ALK-02	SM 2510B/4500H/2320B
Coliforms - DC Media (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-21	ECTC-001	MECP E3407
DOC/DIC (Liquid)	1	OTTAWA	MMACMILLAN	2024-Oct-25	C-OC-01	EPA 415.2
Fecal Coliforms (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-21	FC-001	SM 9222D
Ion Balance (Calc)	1	OTTAWA	ASCHNEIDER		CP-028	MECP E3196
ICP/OES (Liquid)	1	OTTAWA	APRUDYVUS	2024-Oct-22	D-ICP-01	SM 3120B
Ammonia (Liquid)	1	KINGSTON	JYEARWOOD	2024-Oct-22	NH3-001	SM 4500NH3
Turbidity (Liquid)	1	OTTAWA	PLUSSIER	2024-Oct-23	A-TURB-01	SM 2130B

R.L. = Reporting Limit
NC = Not Calculated
Test methods may be modified from specified reference method unless indicated by an *

Michelle Dubien
Data Specialist

Parameter	Units	R.L.	Limits	DWG	Client I.D.: A360959 Sample I.D.: 24-032854-1 Date Collected: 2024-Oct-21 -
Total Coliform (DC Media)	CFU/100mL	1	0	MAC	0
E coli (DC Media)	CFU/100mL	1	0	MAC	0
Background (DC Media)	CFU/100mL	1			7
Fecal Coliform	CFU/100mL	1	0	MAC	0
Alkalinity(CaCO3) to pH4.5	mg/L	5	500	OG	279
TDS (Calc. from Cond.)	mg/L	3	500	AO	409
Conductivity @25°C	uS/cm	1			781
pH @25°C	pH units	-	8.5	OG	8.14
Colour	TCU	2	5	AO	<2
Turbidity	NTU	0.1	5	AO	0.5
Fluoride	mg/L	0.1	1.5	MAC	<0.1
Chloride	mg/L	0.5	250	AO	49.8
Nitrate (N)	mg/L	0.05	10.0	MAC	1.08
Nitrite (N)	mg/L	0.05	1.0	MAC	<0.05
Sulphate	mg/L	1	500	AO	64
Ammonia (N)-Total (NH3+NH4)	mg/L	0.05			<0.05
Dissolved Organic Carbon	mg/L	0.2	5	AO	1.5
Hardness (as CaCO3)	mg/L as CaCO3	0.02	100, 500	OG, D55	385
Calcium	mg/L	0.02			94.4
Iron	mg/L	0.005	0.3	AO	0.027
Magnesium	mg/L	0.02			36.2

Michelle Dubien
Data Specialist

Parameter	Units	R.L.	Limits	DWG	Client I.D. A360959
					Sample I.D. 24-032854-1
					Date Collected 2024-Oct-21
Manganese	mg/L	0.001	0.05	AO	0.007
Potassium	mg/L	0.1			3.1
Sodium	mg/L	0.2	200, 20	AO, MAC	15.0
Anion Sum	meq/L	-			8.39
Cation Sum	meq/L	-			8.42
% Difference	%	-			0.215
TDS (Ion Sum Calc)	mg/L	1	500	AO	435
Conductivity Calc	µmho/cm	-			789

DWG - Drinking Water Guidelines
ODWS - Ontario Drinking Water Standards
AO - Aesthetic Objectives
IMAC - Interim Maximum Acceptable Concentration
MAC - Maximum Acceptable Concentration
ODWO - D-5-5 Objective
OG - Operational Guidelines
WL - Warning Level - Sodium Restricted Diets

Summary of Exceedances

Operational Guidelines

A360959	Found Value	Limit
Hardness (as CaCO3)	385	100

Michelle Dubien
Data Specialist

CADUCEON ENVIRONMENTAL LABORATORIES
Client committed. Quality assured. Canadian owned.

CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: G 130350 **REPORT No: 24-033331 - Rev. 0**

Report To:
Pinchin Ltd. - Kingston
1456 Centennial Dr, Suite 2
Kingston, ON K7P 0K4

CADUCEON Environmental Laboratories
285 Dalton Ave
Kingston, ON K7K 6Z1

Attention: Phil Tibble

DATE RECEIVED: 2024-Oct-23
DATE REPORTED: 2024-Oct-29
SAMPLE MATRIX: Ground Water

CUSTOMER PROJECT: 283258001
P.O. NUMBER:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	1	OTTAWA	PCURIEL	2024-Oct-25	A-IC-01	SM 4110B
Colour (Liquid)	1	OTTAWA	STAILLON	2024-Oct-25	A-COL-01	SM 2120C
Cond/pH/Alk Auto (Liquid)	1	OTTAWA	SBOUDREAU	2024-Oct-25	COND-02/PH-02/ALK-02	SM 2510B/4500H/2320B
Coliforms - DC Media (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-23	ECTC-001	MECP E3407
DOC/DIC (Liquid)	1	OTTAWA	SLOZO	2024-Oct-28	C-OC-01	EPA 415.2
Fecal Coliforms (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-23	FC-001	SM 9222D
Ion Balance (Calc)	1	OTTAWA	ASCHNEIDER		CP-028	MECP E3196
ICP/OES (Liquid)	1	OTTAWA	APRUDYVUS	2024-Oct-25	D-ICP-01	SM 3120B
Ammonia (Liquid)	1	KINGSTON	JYEARWOOD	2024-Oct-24	NH3-001	SM 4500NH3
Turbidity (Liquid)	1	OTTAWA	STAILLON	2024-Oct-24	A-TURB-01	SM 2130B

R.L. = Reporting Limit
NC = Not Calculated
Test methods may be modified from specified reference method unless indicated by an *

Michelle Dubien
Data Specialist

		Client I.D.	A360960
		Sample I.D.	24-033331-1
		Date Collected	2024-10-23
Parameter	**Units**	**R.L.**	-
Total Coliform (DC Media)	CFU/100mL	1	0
E coli (DC Media)	CFU/100mL	1	0
Background (DC Media)	CFU/100mL	1	0
Fecal Coliform	CFU/100mL	1	0
Alkalinity(CaCO3) to pH4.5	mg/L	5	277
TDS (Calc. from Cond.)	mg/L	3	385
Conductivity @25°C	uS/cm	1	737
pH @25°C	pH units	-	7.99
Colour	TCU	2	<2
Turbidity	NTU	0.1	1.2
Fluoride	mg/L	0.1	<0.1
Chloride	mg/L	0.5	39.3
Nitrate (N)	mg/L	0.05	<0.05
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	58
Ammonia (N)-Total (NH3+NH4)	mg/L	0.05	0.13
Dissolved Organic Carbon	mg/L	0.2	2.4
Hardness (as CaCO3)	mg/L	0.02	357
Calcium	mg/L	0.02	84.0
Iron	mg/L	0.005	0.100
Magnesium	mg/L	0.02	35.7



Michelle Dubien
Data Specialist

Parameter	Units	R.L.	Client I.D.: A360960	Sample I.D.: 24-033331-1	Date Collected: 2024-10-23
			-		
Manganese	mg/L	0.001	0.008		
Potassium	mg/L	0.1	3.9		
Sodium	mg/L	0.2	11.3		
Anion Sum	meq/L	-	7.83		
Cation Sum	meq/L	-	7.74		
% Difference	%	-	0.612		
TDS (Ion Sum Calc)	mg/L	1	398		
Conductivity Calc	µmho/cm	-	727		

Michelle Dubien
Data Specialist

CADUCEON ENVIRONMENTAL LABORATORIES
Client committed. Quality assured. Canadian owned.

CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: G 130362 **REPORT No: 24-033470 - Rev. 0**

Report To:
Pinchin Ltd. - Kingston
1456 Centennial Dr, Suite 2
Kingston, ON K7P 0K4

CADUCEON Environmental Laboratories
285 Dalton Ave
Kingston, ON K7K 6Z1

Attention: Phil Tibble

DATE RECEIVED: 2024-Oct-24
DATE REPORTED: 2024-Nov-04
SAMPLE MATRIX: Ground Water

CUSTOMER PROJECT: 283258001
P.O. NUMBER:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	1	OTTAWA	LMACGREGOR	2024-Oct-28	A-IC-01	SM 4110B
Colour (Liquid)	1	OTTAWA	STAILLON	2024-Oct-30	A-COL-01	SM 2120C
Cond/pH/Alk Auto (Liquid)	1	OTTAWA	SBOUDREAU	2024-Oct-28	COND-02/PH-02/ALK-02	SM 2510B/4500H/2320B
Coliforms - DC Media (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-24	ECTC-001	MECP E3407
DOC/DIC (Liquid)	1	OTTAWA	MMACMILLAN	2024-Nov-01	C-OC-01	EPA 415.2
Fecal Coliforms (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-24	FC-001	SM 9222D
Ion Balance (Calc)	1	OTTAWA	TPRICE		CP-028	MECP E3196
ICP/OES (Liquid)	1	OTTAWA	NHOGAN	2024-Oct-28	D-ICP-01	SM 3120B
Ammonia (Liquid)	1	KINGSTON	JYEARWOOD	2024-Nov-01	NH3-001	SM 4500NH3
Turbidity (Liquid)	1	OTTAWA	PLUSSIER	2024-Oct-28	A-TURB-01	SM 2130B

R.L. = Reporting Limit
NC = Not Calculated
Test methods may be modified from specified reference method unless indicated by an *

Michelle Dubien
Data Specialist

		Client I.D.	A360957
		Sample I.D.	24-033470-1
		Date Collected	2024-10-24
Parameter	**Units**	**R.L.**	-
Total Coliform (DC Media)	CFU/100mL	1	0
E coli (DC Media)	CFU/100mL	1	0
Background (DC Media)	CFU/100mL	1	0
Fecal Coliform	CFU/100mL	1	0
Alkalinity(CaCO3) to pH4.5	mg/L	5	262
TDS (Calc. from Cond.)	mg/L	3	330
Conductivity @25°C	uS/cm	1	636
pH @25°C	pH units	-	8.08
Colour	TCU	2	<2
Turbidity	NTU	0.1	2.5
Fluoride	mg/L	0.1	<0.1
Chloride	mg/L	0.5	23.3
Nitrate (N)	mg/L	0.05	0.05
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	38
Ammonia (N)-Total (NH3+NH4)	mg/L	0.05	0.20
Dissolved Organic Carbon	mg/L	0.2	1.7
Hardness (as CaCO3)	mg/L	0.02	311
Calcium	mg/L	0.02	74.8
Iron	mg/L	0.005	0.214
Magnesium	mg/L	0.02	30.1



Michelle Dubien
Data Specialist

			Client I.D.	A360957
			Sample I.D.	24-033470-1
			Date Collected	2024-10-24
Parameter	Units	R.L.		-
Manganese	mg/L	0.001		0.009
Potassium	mg/L	0.1		4.2
Sodium	mg/L	0.2		8.0
Anion Sum	meq/L	-		6.68
Cation Sum	meq/L	-		6.67
% Difference	%	-		0.0348
TDS (Ion Sum Calc)	mg/L	1		336
Conductivity Calc	µmho/cm	-		620

Michelle Dubien
Data Specialist

CADUCEON ENVIRONMENTAL LABORATORIES
Client committed. Quality assured. Canadian owned.

CERTIFICATE OF ANALYSIS

Final Report

C.O.C.: G 131064

REPORT No: 24-033583 - Rev. 0

Report To:
Pinchin Ltd. - Kingston
1456 Centennial Dr, Suite 2
Kingston, ON K7P 0K4

CADUCEON Environmental Laboratories
285 Dalton Ave
Kingston, ON K7K 6Z1

Attention: Phil Tibble

DATE RECEIVED: 2024-Oct-25
DATE REPORTED: 2024-Nov-01
SAMPLE MATRIX: Ground Water

CUSTOMER PROJECT: 283258001
P.O. NUMBER:

Analyses	Qty	Site Analyzed	Authorized	Date Analyzed	Lab Method	Reference Method
Anions (Liquid)	1	OTTAWA	PCURIEL	2024-Oct-28	A-IC-01	SM 4110B
Colour (Liquid)	1	OTTAWA	STAILLON	2024-Oct-31	A-COL-01	SM 2120C
Cond/pH/Alk Auto (Liquid)	1	OTTAWA	SBOUDREAU	2024-Oct-29	COND-02/PH-02/ALK-02	SM 2510B/4500H/2320B
Coliforms - DC Media (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-25	ECTC-001	MECP E3407
DOC/DIC (Liquid)	1	OTTAWA	MMACMILLAN	2024-Oct-31	C-OC-01	EPA 415.2
Fecal Coliforms (Liquid)	1	KINGSTON	BBURTCH	2024-Oct-25	FC-001	SM 9222D
Ion Balance (Calc)	1	OTTAWA	ASCHNEIDER		CP-028	MECP E3196
ICP/OES (Liquid)	1	OTTAWA	APRUDYVUS	2024-Oct-31	D-ICP-01	SM 3120B
Ammonia (Liquid)	1	KINGSTON	KDIBBITS	2024-Oct-31	NH3-001	SM 4500NH3
Turbidity (Liquid)	1	OTTAWA	PLUSSIER	2024-Oct-29	A-TURB-01	SM 2130B

R.L. = Reporting Limit
NC = Not Calculated
Test methods may be modified from specified reference method unless indicated by an *

Michelle Dubien
Data Specialist

Parameter	Units	R.L.	Client I.D.: A360958 Sample I.D.: 24-033583-1 Date Collected: 2024-10-25 -
Total Coliform (DC Media)	CFU/100mL	1	0
E coli (DC Media)	CFU/100mL	1	0
Background (DC Media)	CFU/100mL	1	6
Fecal Coliform	CFU/100mL	1	0
Alkalinity(CaCO3) to pH4.5	mg/L	5	260
TDS (Calc. from Cond.)	mg/L	3	349
Conductivity @25°C	uS/cm	1	672
pH @25°C	pH units	-	8.17
Colour	TCU	2	3
Turbidity	NTU	0.1	2.0
Fluoride	mg/L	0.1	<0.1
Chloride	mg/L	0.5	19.9
Nitrate (N)	mg/L	0.05	<0.05
Nitrite (N)	mg/L	0.05	<0.05
Sulphate	mg/L	1	61
Ammonia (N)-Total (NH3+NH4)	mg/L	0.05	0.20
Dissolved Organic Carbon	mg/L	0.2	1.8
Hardness (as CaCO3)	mg/L	0.02	343
Calcium	mg/L	0.02	90.8
Iron	mg/L	0.005	0.131
Magnesium	mg/L	0.02	28.2



Michelle Dubien
Data Specialist

Parameter	Units	R.L.	Client I.D.: A360958	Sample I.D.: 24-033583-1	Date Collected: 2024-10-25
			-		
Manganese	mg/L	0.001	0.144		
Potassium	mg/L	0.1	8.0		
Sodium	mg/L	0.2	39.8		
Anion Sum	meq/L	-	7.02		
Cation Sum	meq/L	-	8.80		
% Difference	%	-	11.3		
TDS (Ion Sum Calc)	mg/L	1	404		
Conductivity Calc	µmho/cm	-	732		

Michelle Dubien
Data Specialist

745 Development Drive Unit 4B
Kingston, ON
K7M 4W6

Sieve Analysis (LS-602)



Sieve Opening	% Passing
63.0 mm	100
53.0 mm	100
37.5 mm	100
26.5 mm	100
19.0 mm	97
16.0 mm	97
13.2 mm	97
9.5 mm	97
6.7 mm	97
4.75 mm	96
2.36 mm	96
1.18 mm	95
600 µm	89
300 µm	72
150 µm	51
75 µm	32

Silt and Clay (%)	Sand (%)	Gravel (%)
32	64	4
silty SAND, trace gravel		

Lab No: SA24-097
Client: Pinchin
Project No: 1812
Sample ID: TP1
Location: -
Coefficient of Uniformity, Cu: n/a

Effective size, D10 (mm): n/a

Tested: TB
Date: 2024-12-10
Validated:
Date: 12/12/2024

Notes: Estimated T-time: 8 - 20 mins/cm

T-time is estimated from grain size data only, in comparison to OBC 2012 SB-6, and based solely on the sample as received.

745 Development Drive Unit 4B
Kingston, ON
K7M 4W6

Sieve Analysis (LS-602)



Sieve Opening	% Passing
63.0 mm	100
53.0 mm	100
37.5 mm	100
26.5 mm	96
19.0 mm	94
16.0 mm	94
13.2 mm	92
9.5 mm	89
6.7 mm	88
4.75 mm	86
2.36 mm	84
1.18 mm	81
600 µm	76
300 µm	64
150 µm	41
75 µm	24

Silt and Clay (%)	Sand (%)	Gravel (%)
24	63	14
silty, clayey SAND, some gravel		

Lab No: SA24-097A
Client: Pinchin
Project No: 1812
Sample ID: TP5
Location: -
Coefficient of Uniformity, Cu: n/a

Effective size, D10 (mm): n/a

Tested: TB
Date: 2024-12-10
Validated:
Date: 12/12/2024

Notes: Estimated T-time: 8 - 20 mins/cm

T-time is estimated from grain size data only, in comparison to OBC 2012 SB-6, and based solely on the sample as received.

745 Development Drive Unit 4B
Kingston, ON
K7M 4W6

Sieve Analysis (LS-602)



Sieve Opening	% Passing
63.0 mm	100
53.0 mm	100
37.5 mm	100
26.5 mm	100
19.0 mm	93
16.0 mm	93
13.2 mm	91
9.5 mm	89
6.7 mm	87
4.75 mm	85
2.36 mm	83
1.18 mm	75
600 µm	59
300 µm	44
150 µm	29
75 µm	19

Silt and Clay (%)	Sand (%)	Gravel (%)
19	66	15
SAND, some gravel, some silt and clay		

Lab No: SA24-097B
Client: Pinchin
Project No: 1812
Sample ID: TP7
Location: -
Coefficient of Uniformity, Cu: n/a

Effective size, D10 (mm): n/a

Tested: TB
Date: 2024-12-10
Validated:
Date: 12/12/2024

Notes: Estimated T-time: 8 - 20 mins/cm

T-time is estimated from grain size data only, in comparison to OBC 2012 SB-6, and based solely on the sample as received.

745 Development Drive Unit 4B
Kingston, ON
K7M 4W6

Sieve Analysis (LS-602)



Sieve Opening	% Passing
63.0 mm	100
53.0 mm	100
37.5 mm	100
26.5 mm	100
19.0 mm	99
16.0 mm	99
13.2 mm	99
9.5 mm	95
6.7 mm	92
4.75 mm	90
2.36 mm	87
1.18 mm	83
600 µm	73
300 µm	57
150 µm	41
75 µm	28

Silt and Clay (%)	Sand (%)	Gravel (%)
28	62	10
silty, clayey SAND, some gravel		

Lab No: SA24-097C
Client: Pinchin
Project No: 1812
Sample ID: TP8
Location: -
Coefficient of Uniformity, Cu: n/a

Effective size, D10 (mm): n/a

Tested: TB
Date: 2024-12-10
Validated:
Date: 12/12/2024

Notes: Estimated T-time: 8 - 20 mins/cm

T-time is estimated from grain size data only, in comparison to OBC 2012 SB-6, and based solely on the sample as received.

Log of Borehole: BH1

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value (20, 40, 60)	Shear Strength kPa (100, 200)	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 50 mm	0.00											
		Glacial Till Silty sand, some gravel, some clay, brown, damp, compact	0.05	No Monitoring Well Installed	SS	1	20	20						
		End of Borehole	0.30											
		Borehole terminated at 0.30 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH2

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value □ 20 40 60 □	Shear Strength △ kPa △ 100 200	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 50 mm	0.00											
		Glacial Till Silty sand, some gravel, some clay, brown, damp, loose	0.05	No Monitoring Well Installed	SS	1	30	7	□		13.7			Hyd.
		End of Borehole	0.61											
		Borehole terminated at 0.61 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc.

Grade Elevation: N/A

Drilling Method: Solid Stem Auger/Split Spoon

Top of Casing Elevation: N/A

Well Casing Size: N/A

Sheet: 1 of 1

Log of Borehole: BH3

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value (20, 40, 60)	Shear Strength kPa (100, 200)	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 75 mm	0.00											
		Glacial Till Silty sand, some gravel, some clay, brown, moist, loose	0.08	No Monitoring Well Installed	SS	1	20	7						
		End of Borehole	0.46											
		Borehole terminated at 0.46 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH4

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value (□ 20 40 60 □)	Shear Strength (△ kPa △ 100 200)	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 75 mm	0.00	▲ No Monitoring Well Installed										
		Glacial Till Silty sand, some gravel, some clay, brown, damp, compact	0.08		SS	1	30	22	□					
		End of Borehole	0.30	▼										
		Borehole terminated at 0.30 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH5

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value □ 20 40 60 □	Shear Strength △ kPa △ 100 200	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 50 mm	0.00											
		Glacial Till Silty sand, some gravel, some clay, brown, damp, compact	0.05	No Monitoring Well Installed	SS	1	50	26	□					
		End of Borehole	0.61											
		Borehole terminated at 0.61 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH6

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value □ 20 40 60 □	Shear Strength △ kPa △ 100 200	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 75 mm	0.00											
		Glacial Till Gravelly, silty sand, trace clay, brown, damp, compact	0.08	No Monitoring Well Installed	SS	1	30	15	□		12.0			Hyd.
		End of Borehole Borehole terminated at 0.46 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.	0.46											
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH7

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value □ 20 40 60 □	Shear Strength △ kPa △ 100 200	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 75 mm	0.00											
		Glacial Till Gravelly, silty sand, trace clay, brown, damp, compact	0.08	No Monitoring Well Installed	SS	1	40	15	□					
		End of Borehole Borehole terminated at 0.46 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.	0.46											
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH8

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value (□ 20 40 60 □)	Shear Strength (△ kPa △ 100 200)	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface		No Monitoring Well Installed										
		Organics ~ 150 mm	0.00											
		Glacial Till Silty sandy gravel, trace clay, brown, damp, very dense	0.15		SS	1	80	95						
		End of Borehole	0.61											
		Borehole terminated at 0.61 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1

Log of Borehole: BH9

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value (20, 40, 60)	Shear Strength △ kPa △ (100, 200)	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 75 mm	0.00	No MW Installed										
		Glacial Till Silty sandy gravel, trace clay, brown, damp, loose	0.08		SS	1	10	5	□		7.2			Hyd.
		End of Borehole	0.15											
		Borehole terminated at 0.15 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.												
1														

Contractor: Canadian Environmental Drilling and Contractors Inc.

Grade Elevation: N/A

Drilling Method: Solid Stem Auger/Split Spoon

Top of Casing Elevation: N/A

Well Casing Size: N/A

Sheet: 1 of 1

Log of Borehole: BH10

Project #: 283258.002 **Logged By:** MK

Project: Geotechnical Investigation

Client: 1503948 Ontario Inc.

Location: 9243 McArton Road, Almonte, ON

Drill Date: September 15, 2022 **Project Manager:** WT

SUBSURFACE PROFILE					SAMPLE									
Depth (m)	Symbol	Description	Elevation (m)	Monitoring Well Details	Sample Type	Sampler #	Recovery (%)	SPT N-Value	Standard Penetration N-Value (□ 20 40 60 □)	Shear Strength (△ kPa △ 100 200)	Water Content (%)	Sample ID	Soil Vapour Concentration (ppm)	Laboratory Analysis
0		Ground Surface												
		Organics ~ 150 mm	0.00	No Monitoring Well Installed										
		Glacial Till Silty sandy gravel, trace clay, brown, damp, dense	0.15		SS	1	60	31	□					
		End of Borehole Borehole terminated at 0.46 mbgs due to auger refusal on probable bedrock. At drilling completion, groundwater was not encountered.	0.46											
1														

Contractor: Canadian Environmental Drilling and Contractors Inc. **Grade Elevation:** N/A

Drilling Method: Solid Stem Auger/Split Spoon **Top of Casing Elevation:** N/A

Well Casing Size: N/A **Sheet:** 1 of 1